SYNTHESIS OF Bi₂Te₃ NANOCOMPOSITES REINFORCED WITH MWCNTs

Thesis Submitted in partial fulfillment of the requirements for the degree

Of

MASTER OF TECHNOLOGY

In

NANO SCIENCE & TECHNOLOGY

Submitted by

HEMENDRA NATH JAISWAL

(2K13/NST/11)

Under the Supervision of

Internal Supervisor

Dr. AMRISH K. PANWAR (Assistant Professor) Department of Applied Physics DTU, Delhi

External Supervisor

Dr. SUKHVIR SINGH (Sr. Principal Scientist and Head) Electron and Ion Microscopy Section CSIR-NPL, New Delhi



DEPARTMENT OF APPLIED PHYSICS DELHI TECHNOLOGICAL UNIVERSITY, SHAHBAD, DAULATPUR, DELHI - 110042 JULY (2015)



CERTIFICATE

This is to certify that project work entitled "Synthesis of Bi₂Te₃ Nanocomposites reinforced with MWCNTs" is an authentic record of the work carried out by Hemendra Nath Jaiswal (Roll No – 2K13/NST/11) in partial fulfillment of the requirement for the award of the degree of MASTER OF TECHNOLOGY (Nano Science and Technology), Delhi Technological University, Delhi under my guidance and supervision. All research work has been carried out at Electron and Ion Microscopy Section of CSIR-NPL, New Delhi.

Dr. Amrish K. Panwar

(Assistant Professor)

Department of Applied Physics

Delhi Technological University

Delhi-110042.

Prof. Dr. S. C. Sharma

(Head of Department)

Department of Applied Physics

Delhi Technological University

Delhi-110042.

Council of Scientific and Industrial Research, Dr. K.S. Krishnan Road, New Delhi – 110012

CERTIFICATE

This is to certify that Hemendra Nath Jaiswal, M.Tech (Nano Science and Technology) student of Delhi Technological University, Delhi has completed the dissertation entitled "Synthesis of Bi₂Te₃ Nanocomposites reinforced with MWCNTs" under the supervision of Dr. Sukhvir Singh, Sr. Principal Scientist & Head, Electron and Ion Microscopy Section at CSIR-NPL, New Delhi. The above said project has been carried out during the period of January 2015 to June 2015.

During the tenure of his project training he displayed high professionalism and discipline towards his job. He has shown full dedication and commitment during his training.

I wish him all the best in his future endeavors.

Dr. Sukhvir Singh

Sr. Principal Scientist & Head

Electron and Ion Microscopy Section

CSIR-NPL, New Delhi.

TABLE OF CONTENTS

Declaration	(viii)
Acknowledgement	(ix)
List of figure	(x-xii)
List of table	
List of equations	(xiv)
Chapter 1: Introduction	15
1.1 Thermoelectric material	16
1.2 Thermoelectric effects.	18
1.2.1 Seebeck effect.	18
1.2.2 Peltier effect	20
1.2.3 Thomson effect	21
1.3 Thermoelectric characteristic features	22
1.3.1 Power factor	22
1.3.2 Device efficiency	22
1.3.3 Phonon-glass, electron-crystal behavior	23
1.3.4 Effect of semiconductor behaviors	24
1.3.5 Thermal conductivity	24
1.3.6 Electrical conductivity	24
1.3.7 State density	25

1.4 Figure of Merit (ZT)	25
1.5 Application and uses	26
1.5.1 Power generation	26
1.5.2 Refrigeration	27
1.5.3 Temperature measurement	27
1.5.4 Thermal cycler for polymerase chain reaction	27
Chapter 2: Literature Review	28
2.1 Bismuth Telluride - Thermoelectric materials	29
2.2 Structure of Bismuth Telluride.	30
2.3 Properties as Thermoelectric Materials	31
2.4 Improving Figure of Merit (ZT)	33
2.5 Carbon Nanotubes (CNTs).	34
2.5.1 Types of Carbon Nanotubes	35
2.6 Reason for using CNTs.	37
Chapter 3: Synthesis	38
3.1 Phase Diagram	39
3.2 Directional Solidification	40
3.3 Synthesis of Bismuth telluride Compound	41
3.4 Ball Milling Method.	43
3.5 Pellets formation by Spark Plasma Sintering.	44
3.6 Synthesis of Bismuth telluride and MWCNTs Nanocomposites	46

Chapter 4: Chara	acterization techniques	47
4.1 X-ray Dif	fraction(XRD)	48
4.2 Scanning	Electron Microscope	51
4.2.1	Resolution and magnification of SEM	53
4.2.2 En	nergy Dispersive Spectrometer(EDS):Elemental Analysis	54
4.3 Transmiss	sion Electron Microscope	56
4.4 Electron I	Diffraction	57
4.5 Hot Probe	method (P-N type tester)	59
4.6 Measuren	nent of Thermal Conductivity	60
4.6.1	Laser Flash Method	61
4.7 Seebeck (Coefficient Measurement System	62
Chapter 5: Resul	t & discussion	64
5.1 Character	ization of 1.5% by weight CNT reinforced Bi ₂ Te ₃	65
5.1.1	XRD Analysis	65
5.1.2	SEM Analysis	67
5.1.3	EDS Spectra.	68
5.1.4	HRTEM Analysis	69
5.2 Characte	erization of 3% by weight CNT reinforced Bi ₂ Te ₃	71
5.2.1	XRD Analysis.	71
5.2.2	SEM Analysis	73
5.2.3	EDS Spectra	74
5.2.4	HRTEM Analysis	75

References	91-100
Chapter 6: Conclusions	88-90
5.4.3 Electrical Conductivity Measurement	85
5.4.2 Seebeck's Coefficient Measurement	83
5.4.1 Thermal Conductivity Measurement	81
5.4 Determination of Thermoelectric Parameters	81
5.3 Raman Spectrum	76-80

DECLARATION

I hereby declare that this project report entitled "Synthesis of Bi₂Te₃ Nanocomposites reinforced with MWCNTs" is an authentic report of the work done by me under the guidance of Dr. Amrish K. Panwar (Internal Supervisor), Assistant Professor, Delhi Technological University, Delhi and Dr. Sukhvir Singh (External Supervisor), Sr. Principal Scientist and Head, Electron and Ion Microscopy Section, CSIR-National Physical Laboratory, New Delhi.It is an original and independent work and I hereby declare that it has not previously formed the basis for the award of any other degree, diploma, etc. of any university or institution.

Hemendra Nath Jaiswal

ACKNOWLEDGEMENT

I gratefully acknowledge our indebtedness to our guide **Dr. Amrish K. Panwar (Assistant Professor, DTU, Delhi** for his valuable suggestions and support which enabled me to complete the project. A special thanks to **Dr. Sukhvir Singh (Sr. Principal Scientist & Head, Electron and Ion Microscopy Section, CSIR-NPL, New Delhi** whose guidance, stimulating suggestions and encouragement helped me to coordinate my project especially in writing this report. My sincere thanks to those who have provided there support and collaboration to carry out my project work at CSIR-National Physical Laboratory.

I would also like to acknowledge with much appreciation the crucial role of Mr. K. N. Sood and Mr. Dinesh Singh of Electron & Ion Microscopy Section, CSIR-National Physical Laboratory for providing the permission to use all required equipment and the necessary materials to complete my dissertation work. I also thanks my fellow colleagues in the group for their valuable suggestions. A special thanks to Mr. Sandeep Pundir (Phd. Scholar) who constantly helped and suggested me throughout my project work. I also thanks my friend Ripudaman Dixit for continuous motivation and suggestions.

Last but not the least, many thanks to my parents and friends who always help me and contributed a major driving force behind the completion of this project.

Hemendra Nath Jaiswal

List of Figures

Chapter 1

Figure 1.1: Seebeck effect

Figure 1.2: Peltier effect

Chapter 2

Figure 2.1: Showing the ZT values with respect to temperature for various thermoelectric materials studied.

Figure 2.2: Layered structure of a Bi₂Te₃ crystal in hexagonal system.

Figure 2.3: Single-walled and multi-walled CNTs.

Figure 2.4: Types of Single-walled CNTs.

Chapter 3

Figure 3.1: Phase diagram of Bi₂Te_{3.}

Figure 3.2: Vertical Directional Solidification.

Figure 3.3: VDS grown Bismuth Telluride ingot.

Figure 3.4: High temperature furnace (vertical muffle furnace).

Figure 3.5: Quartz Ampoule

Figure 3.6: SEM micrograph of layered structure.

Figure 3.7: Shows the EDS spectra of bulk sample grown

Figure 3.8: Ball Milling Process.

Figure 3.9: Spark Plasma Sintering.

Chapter 4

Figure 4.1: Schematic diagram and picture of XRD setup at NPL.

Figure 4.2: Bragg Reflections.

Figure 4.3: XRD spectrum of Bi₂Te_{3.}

Figure 4.4: Schematic Diagram of electron-sample interaction.

Figure 4.5: Ray diagram of SEM working.

Figure 4.6: SEM (with EDS) facility at NPL

Figure 4.7: High ResolutionTransmission electron microscope(HRTEM).

Figure 4.8: SAED patterns for different materials.

Figure 4.9: Sketch of Hot Probe.

Figure 4.10: Experimental setup of P/N type tester.

Figure 4.11: Laser Flash Method Setup at NPL.

Figure 4.12: Seebeck's Coefficient Measurement Setup at NPL.

Chapter 5

Figure 5.1:XRD pattern of 1.5% by weight CNT reinforced Bi₂Te₃.

Figure 5.2:SEM images of 1.5% by weight CNT reinforced Bi₂Te₃.

Figure 5.3: EDS Spectra of 1.5% by weight CNT reinforced Bi₂Te₃.

Figure 5.4: HRTEM images of 1.5% by weight CNT reinforced Bi₂Te₃.

Figure 5.5: SAEDP of 1.5% by weight CNT reinforced Bi₂Te₃.

Figure 5.6:XRD pattern of 3% by weight CNT reinforced Bi₂Te₃.

Figure 5.7:SEM images of 3% by weight CNT reinforced Bi₂Te₃.

Figure 5.8: EDS Spectra of 3% by weight CNT reinforced Bi₂Te₃.

- **Figure 5.9:** HRTEM images of 3% by weight CNT reinforced Bi₂Te₃.
- **Figure 5.10:** SAEDP of 3% by weight CNT reinforced Bi₂Te₃.
- **Figure 5.11:**Raman Spectra of 1.5% by weightCNT reinforced Bi₂Te₃ in spectrum range of 50 to 300 cm⁻¹.
- **Figure 5.12:** Raman Spectra of 1.5% by weight CNT reinforced Bi₂Te₃.
- **Figure 5.13:**Raman Spectra of 3% by weight CNT reinforced Bi₂Te₃ in spectrum range of 50 to 300 cm⁻¹.
- Figure 5.14: Raman Spectra of 3% by weight CNT reinforced Bi₂Te₃.
- **Figure 5.15:** Variation Of Thermal Conductivity with Temperature of 1.5% by weight CNT reinforced Bi₂Te₃ Nanocomposite.
- **Figure 5.16:** Variation Of Thermal Conductivity with Temperature of 3% by weight CNT reinforced Bi₂Te₃ Nanocomposite.
- **Figure 5.17:** Variation Of Seebeck's Coefficient with Temperature of 1.5% by weight CNT reinforced Bi₂Te₃ Nanocomposite.
- **Figure 5.18:** Variation Of Seebeck's Coefficient with Temperature of 3% by weight CNT reinforced Bi₂Te₃ Nanocomposite.
- **Figure 5.19:** Variation Of Electrical Conductivity with Temperature of 1.5% by weight CNT reinforced Bi₂Te₃ Nanocomposite.
- **Figure 5.20:** Variation Of Electrical Conductivity with Temperature of 3% by weight CNT reinforced Bi₂Te₃ Nanocomposite.

List of tables

Chapter 2

- **Table 2.1** Properties of Bismuth Telluride.
- **Table 2.2** Properties of CNTs.

Chapter 5

- **Table 5.1** Crystallite size of 1.5% by weight CNT reinforced Bi₂Te₃.
- **Table 5.2** d spacing of 1.5% by weight CNT reinforced Bi₂Te₃.
- **Table 5.3** Elastic strain of 1.5% by weight CNT reinforced Bi₂Te₃.
- Table 5.4 Crystallite size of 3% by weight CNT reinforced Bi₂Te₃.
- **Table 5.5** d spacing of 3% by weight CNT reinforced Bi₂Te₃.
- **Table 5.6** Elastic Strain of 3% by weight CNT reinforced Bi₂Te₃.
- **Table 5.7** Shows the thermoelectric parameters for ball milled nanostructured Bi₂Te₃.
- **Table 5.8** Shows the thermoelectric parameters for ball milled nanostructured Bi₂Te₃ reinforced with CNTs.

List of Equations

Chapter 1

- **1.1** Figure of Merit.
- **1.2** Peltier Heat.
- **1.3** Heat production in unit volume.
- **1.4** Power Factor
- **1.5** Efficiency of thermoelectric material device.
- **1.6** Maximum Efficiency.
- **1.7** ZT after geometrical optimization.
- **1.8** Thermal Conductivity.
- **1.9** Electrical Conductivity.

Chapter 4

- **4.1** Bragg's Law
- **4.2** Scherrer Equation
- **4.3** Elastic Strain
- **4.4** Thermal Diffusivity