

HYDROGEN FROM BIOMASS: PATHWAYS, PERFORMANCE, AND PROSPECTS

**A Dissertation Submitted
In Partial Fulfillment of the Requirements for the
Award of the Degree**

of

MASTER OF SCIENCE (M.Sc.)

in

CHEMISTRY

by

NEHA SHARMA
(24/MSCCHE/53)

SHIVAM YADAV
(24/MSCCHE/59)

**Under the Supervision of
Prof. Anil Kumar**



Department of Applied Chemistry

DELHI TECHNOLOGICAL UNIVERSITY
(Formerly Delhi College of Engineering)
Shahbad Daulatpur, Main Bawana Road, Delhi-110042. India

June, 2026



DELHI TECHNOLOGICAL UNIVERSITY

(Formerly Delhi College of Engineering)

Shahbad Daulatpur, Main Bawana Road, Delhi-42

DECLARATION

We, **Neha Sharma** (24/MSCCHE/53) and **Shivam Yadav** (24/MSCCHE/59), hereby declare that the work presented in the dissertation entitled “**Hydrogen from Biomass: Pathways, Performance, and Prospects**” is an original work that has been carried out by us during the period from August, 2025 to April, 2026 Delhi Technological University under the supervision of Prof. Anil Kumar.

The research in this dissertation is an authentic record of our work and has been submitted in partial fulfilment of the requirements for the award of the Degree of Master of Science in Chemistry to the Department of Applied Chemistry, Delhi Technological University, New Delhi, India.

The matter presented in the dissertation has not been submitted by us for the award of any other degree of this or any other Institute.

Neha Sharma
24/MSCCHE/53

Shivam Yadav
24/MSCCHE/59



DELHI TECHNOLOGICAL UNIVERSITY

(Formerly Delhi College of Engineering)

Shahbad Daultapur, Main Bawana Road, Delhi-42

CERTIFICATE BY THE SUPERVISOR

Certified that **Neha Sharma** (24/MSCCHE/53) and **Shivam Yadav** (24/MSCCHE/59) have carried out their research work presented in this dissertation entitled “**Hydrogen from Biomass: Pathways, Performance, and Prospects**” for the award of Degree of Master of Science in Chemistry from Department of Applied Chemistry, Delhi Technological University, Delhi, under my supervision. The dissertation embodies results of original work, and studies are carried out by the student themselves and the contents of the dissertation do not form the basis for the award of any other degree to the candidate or to anybody else from this or any other University/Institution.

Prof. Anil Kumar

Supervisor



DELHI TECHNOLOGICAL UNIVERSITY

(Formerly Delhi College of Engineering)

Shahbad Daultapur, Main Bawana Road, Delhi-42

PLAGIARISM VERIFICATION

Title of thesis “**Hydrogen from Biomass: Pathways, Performance, and Prospects**”.

This is to report that the above thesis was scanned for similarity detection.
Process and outcome are given below:

Software used: **Turnitin**

Similarity Index: 4%

Total Word Count: 11,303

Date: 16/06/2026

Neha Sharma

24/MSCCHE/53

Shivam Yadav

24/MSCCHE/59

Prof. Anil Kumar

Supervisor

TABLE OF CONTENTS

<i>Title</i>	<i>Page No.</i>
<i>Declaration</i>	ii
<i>Certificate by the supervisor</i>	iii
<i>Plagiarism Verification</i>	iv
<i>Acknowledgements</i>	v
<i>List of Tables</i>	ix
<i>List of Figures</i>	x
<i>Abbreviations</i>	xi
<i>Abstract</i>	xii
 CHAPTER 1: INTRODUCTION	 1-9
1.1 Background and motivation: global status of renewable energy	3
1.2 Advantages of hydrogen over conventional fuels	7
1.3 Hydrogen production	8
1.3.1 Fossil fuel-based	8
1.3.2 Renewable resources-based	8
 CHAPTER 2: BIOMASS RESOURCES AND FEEDSTOCK CHARACTERISATION	 10-20
2.1 Feedstock overview	11
2.2 Agricultural residues and biowastes	12
2.3 Critical properties of biomass feedstocks	14
2.4 Impact of biomass collection on contamination level	16
2.5 Preprocessing of biomass	16
2.5.1 Physical preprocessing	17

2.5.2 Chemical preprocessing	18
2.5.3 Biological preprocessing	20
CHAPTER 3: BIOMASS CONVERSION PATHWAYS	21-34
3.1 Thermochemical routes	22
3.1.1 Gasification techniques	22
3.1.2 Pyrolysis technique	26
3.2 Biochemical route	29
3.2.1 Dark fermentation	29
3.2.2 Photo fermentation	32
CHAPTER 4: TECHNOLOGY ASSESSMENT AND ECONOMIC EVALUATION	35-39
4.1 Technology readiness level (TRL)	36
4.2 Technoeconomic analysis (TEA)	37
CHAPTER 5: CONCLUSION AND FUTURE SCOPE	40-43
5.1 Merits and demerits of various techniques	41
5.2 Conclusion	42
5.3 Future Scope	43
REFERENCES	44-67
APPENDICES	
List of Publications	I
List Of Conferences/ Seminars	III
Plagiarism Report	V

LIST OF TABLES

Table No.	Description	Page No.
1	Proximate, ultimate, and calorimetric properties of selected lignocellulosic biomass feedstocks relevant to biohydrogen production.	15
2	Hydrogen Production with Different Biomass using Gasification routes.	25
3	Different Biomass used in Hydrogen Production via Pyrolysis.	28
4	Different substrate with hydrogen yield and other parameters via Dark Fermentation.	30
5	The Technology and scale implement in TRL.	37
6	Cost and efficiency for different hydrogen production technologies.	39
7	Merit and Demerit of several techniques.	41

LIST OF FIGURES

Table No.	Description	Page No.
1	Overview of renewable energy types and their practical implementations.	3
2	Status of renewable energy and tradable energy consumption across multiple regions from 2021 to 2024.	4
3	Statistics of renewable energy consumption in different regions. ‘Other region’ includes CIS, the Middle East, and Africa.	5
4	Statistics of renewable energy generation in different regions. ‘Other region’ includes CIS, the Middle East and Africa.	6
5	Statistics of renewable energy generation sources in different regions. ‘Other region’ refers to the CIS, the Middle East and Africa.	6
6	Biomass classification, composition and its suitability for hydrogen production pathways.	11
7	Schematic presentation of hydrogen production using different sources of biomass.	13
8	Overview of chemical composition of various biomass.	16
9	Classification of preprocessing techniques.	17
10	Working Flow Chart of Gasification Techniques.	24
11	Mechanistic pathways of hydrogen formation during biomass pyrolysis.	26
12	Schematic Representation for Pyrolysis.	27
13	Process involved in Dark Fermentation.	31
14	Flow chart for Photo-fermentation.	33
15	Flowchart for TRL.	36

ABBREVIATIONS

CIS	Commonwealth of Independent States
POX	Partial Oxidation of Methane
MeSR	Methanol Steam Reforming
MSR	Methane Steam Reforming
SE-MSR	Sorption Enhanced Methane Steam Reforming
GSR	Glycerol Steam Reforming
HHV	High Heating Value
LHV	Low Heating Value
TRL	Technology Readiness Level
TEA	Techno-Economic Assessment
LCA	Life Cycle Assessment

ABSTRACT

The production of hydrogen from biomass has shown promise as a sustainable energy source. Biomass is abundant, renewable, and carbon-neutral. It can be effectively used as a feedstock for hydrogen production via a variety of conversion processes, such as thermochemical and biological routes. This article provides a comprehensive overview of common biomass-to-hydrogen pathways. These encompass biological processes such as dark fermentation and phototrophic pathways, as well as thermochemical techniques such as gasification and pyrolysis. While biological pathways enable mild operating conditions and interaction with waste treatment systems, thermochemical technologies generally offer better hydrogen yields and greater technological maturity. Important elements that affect process performance are also covered, including feedstock composition, catalyst choice, reactor design, and system integration. It includes TRL and techno assessment analysis along with the merits and demerits of the techniques used for hydrogen production.

Chapter 1

INTRODUCTION

Chapter 1

INTRODUCTION

Nearly 84.5% of the world's energy needs are still met by fossil fuels. In 2023, oil accounted for 32.78% of global energy use, followed by natural gas at 23.96% and coal at 27.79%. Consequently, energy-related greenhouse gas emissions are predicted to reach 378.3 Gt CO₂ in 2024 representing a year-over-year increase of approximately 1% (357 Mt CO₂) [1,2]. As fossil fuel reserves become scarcer, prices increase, and the environmental effects of increasing energy demand escalate, researchers are exploring alternatives to fossil fuels such as low-carbon alternatives and renewable energy resources [3].

The renewable energy industry is regarded today as being one of the cleanest forms of energy available, almost emission-free, because it draws its energy from natural phenomena such as wind, sunlight, biomass, geothermal heat, ocean currents, and hydropower, which are replenished on human timescales and produce significantly lower greenhouse gas emissions than fossil fuels. Globally, final energy demand is divided into four primary sectors: industry, transportation, buildings, and agriculture [4]. In comparison to fossil energy, renewable energy has lower local air pollution burdens, significantly lower lifecycle greenhouse gas emissions, an inexhaustible primary resource base, and often lower operating expenses. The diversification of renewable energy sources also strengthens energy security by reducing dependency on imported fuels. Due to the fact that these technologies are available across most geographies, nearly every nation can deploy some combination of them [5].

Within this landscape, bioenergy is distinctive and can also serve as a feedstock for low-carbon hydrogen, enabling decarbonization beyond the power sector [6]. Hence, renewable forms of energy are the most promising alternative in the coming years. Figure 1 summarizes the principal renewable modalities and typical implementations.




Figure 1: Overview of renewable energy types and their practical implementations.

1.1 Background and Motivation: Global Status of Renewable Energy

The status of primary energy consumption (includes both renewable and non-renewable energy sources) across multiple regions from 2021 to 2024 is presented in Figure 2. The primary energy consumption is highest for Asia Pacific in the world. The regional distribution for consumption of primary energy Asia Pacific (279.24 EJ) > North America (111.75 EJ) > Europe (71.66 EJ) > Middle East (41.43 EJ) > Commonwealth Independent States (41.07 EJ) > Central and South America (26.04 EJ) > Africa (21.03 EJ) in 2024. Global primary energy consumption has exhibited a steady upward trend. Asia Pacific region has recorded an increase of nearly 40 EJ since 2015.




Figure 2: Status of renewable energy and tradable energy consumption across multiple regions from 2021 to 2024.

While the renewable sources include wind energy, solar energy, bioenergy, and geothermal power. The data presented in Figure 3-5 shows a steady annual increase in renewable energy consumption and generation. Renewable energy consumption and generation are highest in the Asia Pacific across all years. The order for renewable energy consumption is Asia Pacific (17.22 EJ) > Europe (10.14 EJ) > North America (8.44 EJ) > South and Central America (3.35 EJ) > Africa (0.47 EJ) > Middle East (0.18 EJ) > Commonwealth of Independent States (0.10 EJ).

With approximately 11.32 EJ, China is the leading consumer of renewable energy in the Asia-Pacific region. This is followed by India (1.79 EJ) and Japan (1.32 EJ). As expected, a similar trend is observed for renewable energy generation. The order of renewable energy generation in 2021 is Asia Pacific (1690.1 TWh) > Europe (946.5 TWh) > North America (714 TWh) > South and Central America (229.3 TWh) > Africa

(49.0 TWh) > Middle East (18.5 TWh) > Commonwealth of Independent States (9.6 TWh).




Figure 3: Statistics of renewable energy consumption in different regions. ‘Other region’ includes CIS, the Middle East, and Africa.

With approximately 1,152.5 TWh, China is the leading renewable energy producer in the Asia-Pacific region. This is followed by India (171.9 TWh) and Japan (130.3 TWh). Wind power accounts for the highest share of renewable electricity production, estimated at approximately 1,596.4 TWh in 2020 and 1,861.9 TWh in 2021 [7]. This is followed by solar energy estimated at about 846.2 TWh in 2020 and 1032.5 TWh in 2021 [8].

Therefore, among low-carbon alternatives including renewable electricity (solar, wind, hydro, geothermal), nuclear power, sustainable bioenergy, direct electrification with batteries, and carbon capture, utilization, and storage, “Hydrogen” is a key to a Carbon neutral future.




Figure 4: Statistics of renewable energy generation in different regions. ‘Other region’ includes CIS, the Middle East and Africa.




Figure 5: Statistics of renewable energy generation sources in different regions. ‘Other region’ refers to the CIS, the Middle East and Africa.

It stands out as a versatile energy carrier for hard-to-abate sectors that can be produced from diverse resources and is amenable to storage and long-distance transport [9]. At the point of use, hydrogen conversion (in fuel cells or via combustion) emits no CO₂; life-cycle emissions depend on the production pathway. When produced by water electrolysis powered by renewable electricity (“green hydrogen”), the life-cycle CO₂ can approach a net-zero carbon footprint, positioning hydrogen as a promising option for decarbonization, as the CO₂ released during combustion is absorbed by plants during photosynthesis [10,11].

This review gives a detailed assessment of the biomass-to-hydrogen value chain. It encompasses feedstock characteristics, preprocessing strategies, thermochemical and biochemical conversion pathways, technology readiness levels (TRLs), and techno-economic considerations. Recent studies are systematically compared across gasification, pyrolysis, dark fermentation, and photo fermentation. Performance indicators such as reactor configuration, catalyst selection, operating conditions, hydrogen yield, gas yield, and tar generation are compared. Additionally, detailed mechanistic pathways for hydrogen generation in both thermochemical and biochemical processes are discussed. Insights regarding reaction behaviour and the determinants of hydrogen production are presented. The study integrates process performance, mechanistic understanding, and commercialization readiness. This review provides the opportunities, limitations, and prospects of biomass-based hydrogen production technologies.

1.2 Advantages of hydrogen over Conventional Fuels

Hydrogen is considered a zero emission source as it burns cleanly and produces water vapour only [12]. The physical and chemical characteristics make it attractive for clean

energy systems. Hydrogen escapes and disperses into the air at a much faster rate in outdoor accidents. As a result it is less likely to accumulate. It remains manageable under controlled conditions despite its wide flammability range (from 4% to 77% by volume) in air [13]. It burns quickly and has a low impact on nearby objects owing to its low heat radiation during combustion. This chemical has a wider explosive range at higher concentrations. Although with the increasing concentration combustion transitions to deflagration rather than a violent explosion [14].

It has a higher energy density due to its lower mass density and heating value of 120 MJ/kg. Hydrogen has a flame propagation rate of approximately 346 cm^{-1} . This is significantly faster than most conventional fuels [15]. Overall hydrogen is a key element in the worldwide decarbonization strategy due to its excellent gravimetric energy density, low carbon footprint in combustion, wide flammability range, and extensive applicability [16].

1.3 Hydrogen Production

The production of hydrogen can be performed using fossil fuels or renewable feedstocks [17].

1.3.1 Fossil fuel-based

Hydrogen can be produced from natural gas, oil and coal where pyrolysis or steam reforming of hydrocarbons takes place. Different methods are available to achieve steam reforming like partial oxidation of methane (POX), methanol steam reforming (MeSR), methane steam reforming (MSR), and sorption-enhanced methane steam reforming (SE-MSR) [18]. Among these, methane steam reforming is the most widely used industrial process due to its high hydrogen yield and established technology.

1.3.2 Renewable resources-based

Water splitting and biomass processing are the two conversion techniques employed for renewable resource based hydrogen production. Several methods are available for splitting water including thermolysis, photolysis and electrolysis [19]. **Biomass processing can be biological such as** glycerol steam reforming (GSR) or thermochemical [20]. It includes bio-photolysis and fermentation [21,22]. **Thermochemical processes:** They include pyrolysis, gasification, and liquefaction [23].

One of the most environmentally friendly and economically viable routes to sustainable hydrogen production is biomass-derived hydrogen, which can be produced using waste biomass and renewable carbon sources [24].

Chapter 2

BIOMASS RESOURCES AND FEEDSTOCK CHARACTERIZATION

Chapter 2

BIOMASS RESOURCES AND FEEDSTOCK CHARACTERIZATION

2.1 Feedstock overview

Biomass is now regarded as an innovative renewable feedstock for producing hydrogen. It can be broadly classified based on origin and composition [25]. This strongly influences their suitability for hydrogen production. Figure 6 presents a flowchart of the main biomass categories. These are forest biomass, agricultural residues, energy crops, industrial and municipal waste, and algal and microbial biomass. Additionally, it presents their characteristic composition and the most suitable hydrogen production pathways.




Figure 6: Biomass classification, composition and its suitability for hydrogen production pathways.

Lignin-rich biomass is generally preferred for thermochemical routes such as gasification and pyrolysis. While carbohydrate-rich and low-lignin biomass is more favourable for biochemical processes such as dark and photo fermentation. Therefore, forest biomass and energy crops favour thermochemical processes. Industrial and municipal waste favour biochemical fermentation. Algal and microbial biomass are ideal for dark and photo fermentation.

Biomass is considered to have a neutral carbon footprint, as the CO₂ released during its production is counteracted by the CO₂ absorbed during growth [26]. The pollution-free nature of this method makes it superior to other methods of hydrogen production. Despite these challenges, cultivar selection, growth period, harvesting, shipping, and pre-treatment costs must be considered. There are a variety of chemical or biological reactions that can occur in biomass sources, resulting in a variations in the production rate and quality of hydrogen [27]. With low sulphur content, agricultural residues and bio-waste offer a cost-effective solution and may become key energy crops for hydrogen generation. In addition, since energy crops don't interfere with food crop production, they are excellent options for generating hydrogen via physicochemical or biological routes. A wide range of sources supply lingo-cellulosic biomass. These include agricultural residues, food wastes, forest byproducts, marine residues, and energy crops. It is estimated that approximately 4.6 billion tons of lignocellulosic biomass are produced from agricultural residues every year, and about 7 billion tons are produced from forest residues [28].

2.2 Agricultural residues and biowastes

They are inexpensive and sustainable feedstocks due to their low sulfur content and wide availability [29]. Additionally, they can be cultivated on marginal land without interfering with food production. Specialized energy crops provide an excellent alternative for hydrogen production via physicochemical and biological conversion pathways [30, 31]. For example forest leftovers, marine biomass, agricultural residues, food and agro-industrial waste and crops cultivated for energy are all sources of lignocellulosic biomass [30]. An estimated 4.6 billion tonnes of lignocellulosic biomass are produced each year globally from agricultural wastes, while an estimated 7 billion tonnes come from forest resources [30, 31]. Globally, it is estimated that approximately 4.6 billion tonnes of lignocellulosic biomass are generated annually from agricultural residues, while around 7 billion tonnes originate from forest resources [31,32]. Figure 7 shows the schematic representation of biomass sources.




Figure 7: Schematic presentation of hydrogen production using different sources of biomass.

2.3 Critical Properties of Biomass Feedstocks

The chemical properties of biomass can vary widely from one feedstock to another, and these differences become especially important when multiple feedstocks are used in the same conversion process. Therefore, the heating value of a biomass sample reflects the amount of lignin present in it. A higher lignin content generally means a higher energy potential. This is due to its highly aromatic and carbon-rich structure. Lodgepole Pine (30.50%) has the highest and Sorghum (16.01%) contains the least lignin content. High lignin content increases thermal resistance. It promotes char formation during pyrolysis. This leads to higher fixed carbon yield and enhanced production of gas-phase products under gasification conditions. The aromatic structure of lignin also contributes to higher energy density. It influences syngas composition including hydrogen formation under steam gasification. This conveys that lignin rich materials such as Lodgepole Pine are more suitable for combustion due to higher energy density [33]. However, the chemical composition of biomass is not determined by species alone. Environmental factors such as climate, soil characteristics and local agricultural conditions also effect biomass quality. Ash content, structural carbohydrate and moisture levels are also affected by variation temperature and rainfall.

Harvesting practices further contribute to these differences. Properties of biomass are influenced by season, equipment used, and timing of harvest. Lower moisture content improves thermochemical processes like co-firing and pyrolysis. Strategic harvest timing can also help maximize carbon content and reducing ash formation at the same time. This trade-off is important to consider. Lower ash is beneficial for combustion

but may not be as favourable for biological processes like fermentation as carbon availability is critical in these cases [34].

Ash content varies significantly across feedstocks. Sugarcane bagasse contains the highest ash content (10.6%) and Hybrid Poplar contains the lowest ash content (0.9%). The method of collection is also important. Biomass harvested manually tends to contain less soil and therefore less ash than biomass collected using large-scale mechanical equipment. To better understand these differences, both manual and commercial harvesting methods should be evaluated especially to quantify the soil uptake during large-scale operations. Table 1 shows an analysis of different parameters using biomass feedstocks.

Table 1: Proximate, ultimate, and calorimetric properties of selected lignocellulosic biomass feedstocks relevant to biohydrogen production.

Attribute → Biomass ↓	Proximate analysis (%)			Ultimate analysis (%)		Calorimetry (kcal/kg)	
	Volatile matter	Ash	Fixed carbon	Hydrogen	Carbon	HHV	LHV
Corn Stover	79.0	4.3	16.7	5.7	48.7	7990	6614
Switchgrass	80.2	4.2	15.6	5.7	47.2	8077	6749
Miscanthus	85.5	1.4	13.1	5.8	50.6	8493	7073
Sorghum	77.8	7.8	14.4	5.6	45.6	7880	6554
Wheat Straw	77.0	9.1	13.9	5.9	45.0	7742	6333
Hybrid Polar	86.5	0.9	12.6	6.0	49.4	8746	7370
Lodge Pole Pine	84.5	1.1	14.4	6.1	50.1	8760	7371
Sugarcane Bagasse	76.0	10.6	13.4	5.4	45.2	7829	6499

2.4 Impact of Biomass Collection on Contamination Level

The mode of collection has a direct impact on the purity of the feedstock. Biomass harvested manually tends to have lower ash and soil content. Material harvested using large-scale commercial machinery can elevate ash levels due to soil intrusion during mechanical cutting and transport. Hence, a combined evaluation of manual and mechanized harvesting systems is crucial for accurately assessing soil contamination and optimizing feedstock handling protocols for sustainable bioenergy production.

Figure 8 presents compositions of various biomass.




Figure 8: Overview of chemical composition of various biomass.

2.5 Preprocessing of Biomass

Substrate selection and conversion technology are key factors that affect the rate of hydrogen production. Among various sources of energy [35]. The biomass-based sustainable fuels stand out as the most viable strategy for achieving sustainable energy

[36]. One of the key stages in the efficient production of biohydrogen from biomass is substrate pretreatment. Physical, chemical, biological, and hybrid pretreatment methods have been employed for efficient hydrogen production [37,38]. Figure 9 presents the classification of preprocessing techniques.




Figure 9: Classification of preprocessing techniques.

2.5.1 Physical Preprocessing

Physical pretreatment includes mechanical milling, heating, freeze–thaw cycles, microwave exposure, ultrasonic treatment, and irradiation. The pretreatment process starts with milling to increase the molecular surface area of the substrate [34]. Milling is carried out before applying chemical, enzymatic, or physicochemical preprocessing. Techniques such as two-roll, hammer, bead, colloid, and disc milling are used in the milling of biomass for hydrogen production [39].

- **Thermal treatment** supports the growth of hydrogen-producing bacteria and simultaneously hinders the activity of methanogens. Time and temperature are critical

factors during pre-treatment optimization. Brief pretreatments at controlled temperatures may effectively inhibit hydrogen-consuming microbes [39,40].

- **Freezing and thawing** processes includes high-pressure or dehydro-freezing, application of antifreeze proteins, induction of ice nucleation and thawing by high-pressure microwave heating [41]. During freezing the temperature is lowered causing a phase shift from liquid to solid while thawing generally occurs at a slower rate than freezing.
- **Microwave radiation** is commonly employed as a preprocessing technique for lignocellulosic feedstocks. The method may be preferred for its ability to operate conveniently, facilitate cellulose breakdown, generate heat rapidly, produce limited inhibitors and reduce energy consumption.
- **Ultrasound treatment** accelerates the process while cutting down on the amount of enzymes or chemicals needed. It is regarded as an innovative and sustainable method providing strong capacity for intensification. This is considered the optimal approach for pre-processing activated sludge for hydrogen production during dark fermentation. The structural damage to lignin and cellulose in biomass is induced by gamma radiation through free radical formation.
- **Irradiation Pretreatment:** The gamma radiation from the radioisotope Cobalt-60 has been utilized to treat substrates for hydrogen generation. Pretreatment of seed sludge with ionizing radiation resulted in peak hydrogen production performance [42].

2.5.2 Chemical preprocessing

The chemical agents employed for biomass pre-processing encompass alkalis, acids, inhibitors of methanogens, chloroform, ozonolysis, acetylene and iodopropane [43].

Alkaline and acidic preprocessing are the most popular adopted strategies for

enhancing hydrogen production efficiency. This is primarily due to their ability to exploit the pH sensitivity of non-sporulating hydrogen-consuming microorganisms [32, [44]. This process facilitates the delignification of biomass, enhances the release of fermentable sugars, and supports efficient generation of biohydrogen. Alkaline treatment disintegrates the crystalline structure of lignocellulosic material by saponifying ester bonds. This results in more efficient hydrolysis. In contrast, acid treatment aids in dissolving hemicellulose but fails to efficiently separate lignin from biomass [45,46]. Preprocessing with a dilute alkali enhances the effectiveness of enzymatic hydrolysis. It also improves the conversion of residual polysaccharides. This enhancement is because of partial delignification and cleavage of ester linkages. It increases the accessibility of cellulose and hemicellulose to hydrolytic enzymes. Additionally disruption of the rigid lignocellulosic structure reduces crystallinity. This allows more efficient enzyme penetration and substrate enzyme interaction.

Methanogen inhibitors allow for the targeted and effective removal of hydrogen consuming methanogens [47,48]. Methanogen inhibitors such as chloroform, iodopropane and acetylene are frequently utilized to suppress the targeted hydrogen consuming methanogens [47].

Chloroform inhibits methanogenesis. It disrupts corrinoid (vitamin B12-dependent) enzymes. These enzymes are involved in key methyl-transfer reactions within methanogenic pathways. This represents an enzymatic level inhibition. Here the activity of corrinoid-dependent proteins is suppressed. This leads to reduced methane formation. Thus lowers hydrogen consumption by methanogens. Hydrogen-producing fermentative bacteria are independent of these methanogen-specific corrinoid-dependent enzymes. Therefore hydrogen production proceeds with limited impact.

Iodopropane acts as a corrinoid (vitamin B12) cofactor antagonist [48]. It interferes directly with the function of B12-containing methyl-carrier systems [41]. These systems are fundamental to methyl transfer processes in methanogenic pathways. Thus iodopropane blocks the cofactor-mediated transfer steps [49]. This results in suppression of methanogenic hydrogen utilization.

Thus hydrogen-producing fermentative bacteria continue to be unaffected. This is because their metabolic pathways for formation of hydrogen does not involve corrinoid (vitamin B12)-dependent methyl-transfer systems targeted by these inhibitors [50]. Acetylene serves as an economical and effective methanogenesis inhibitor in preprocessing and help in hydrogen production [51].

Ozonolysis breaks down lignin and thereby facilitates the hydrolysis of the enzyme into fermentable sugars. It is applied under controlled optimal thermal and pressure settings. It aims at preventing the formation of harmful by-products and supporting sustainable operation [52,53]. Biomass moisture content is the key factor affecting ozone pretreatment as higher moisture levels reduce lignin oxidation [44].

2.5.3 Biological preprocessing

Biological preprocessing lowers energy demand, resulting in superior performance. It is environmental friendly compared to other traditional approaches (physical or chemical) [44]. It facilitates faster hydrolysis by disrupting the lignocellulose substrates [54]. This preprocessing method includes both fungal and enzymatic methods. Various fungal strains, including brown, white, and soft-rot fungi, are used to degrade lignin and hemicellulose [55]. Hydrolysis by an enzyme bypasses the need for fungi by utilizing enzymes to perform the hydrolysis process.

Chapter 3

BIOMASS CONVERSION PATHWAYS

Chapter 3

BIOMASS CONVERSION PATHWAYS

Biomass serves as a promising renewable source for hydrogen generation. It is beneficial for biofuel production because it can improve carbon neutrality. It can be converted into hydrogen either by thermochemical routes or biochemical routes.

3.1 Thermochemical Route


Biomass serves as a promising renewable source for hydrogen generation. It is beneficial for biofuel production because it can improve carbon neutrality. It can be converted into hydrogen either by thermochemical routes or biochemical routes [56,57].

Liquefaction can be classified into solvolysis, hydropyrolysis, and hydrothermal. It is suitable for biomass with a moisture content up to ten folds higher [58]. It is a comparatively unattractive alternative owing to demanding operating conditions and restricted productivity [59]. The ability to tune operating parameters allows pyrolysis to valorise variety of biomass [60].


3.1.1 Gasification technique

It involves thermochemical conversion of biomass into gases like hydrogen, carbon dioxide, carbon monoxide and methane. This outcome is possible when oxygen or steam is introduced under optimised conditions during high-temperature heating of the biomass. It can be air gasification, steam gasification or oxygen gasification. The overall reactions involved are given in equations 1-3 [61,62].


Air gasification:



Steam gasification:





Oxygen gasification:



The dry biomass requires less energy for gasification than wet feedstock. There are various phases of gasification that occur at different temperatures, including drying, pyrolysis, reduction, and combustion [63]. Wet feedstock is dried (250 °C) in the gasifier, releasing water in the process. This is followed by pyrolysis (250-500°C), where gaseous chemicals, such as carbon dioxide and carbon monoxide, and tar are liberated. Here biomass decomposes into char, tar and gaseous compounds such as carbon monoxide and carbon dioxide. These gases subsequently participate in gasification and reforming reactions. Hydrogen is then produced via the reduction process (800-600°C). This is primarily through char-steam gasification and water-gas shift reactions. These convert carbonaceous intermediates and carbon monoxide into hydrogen-rich syngas. Finally the remaining char is subjected to the combustion process (800-1000°C) [64]. Thus, it provides the heat required to sustain the endothermic gasification reactions. Figure 10 represents the working of the reactor.

Reduction Process:





Combustion Process:




Figure 10: Working Flow Chart of Gasification Techniques

The rise in temperature makes gasification an endothermic process requiring substantial energy input. The type of oxidizer determines it as air, oxygen or steam gasification [65]. Generally, air is used as an oxidizer in fixed-type bed reactors resulting in low hydrogen generation due to the presence of a considerable amount of carbon dioxide and nitrogen. Removal of nitrogen reduced the heating value of the fuel [66]. This drawback is overcome oxygen gasification process. However, pure oxygen is quite expensive, which limits its use as an oxidizer [67]. Steam gasification is adopted as an alternative that lies between air and oxygen gasification [21]. Steam gasification generally yields higher hydrogen concentrations. This is because steam participates directly in char-steam gasification and water-gas shift reactions. Both of these promote additional hydrogen formation. The hydrogen level in syngas is strongly


influenced by the type of biomass and the gasification parameters, including temperature, the ratio of steam to biomass, heating rate, type of oxidizer, and reaction time [68]. Table 2 represents hydrogen production using different biomass with its key parameters including reactor configuration, catalysts, gas yield, etc [69].

Table 2: Hydrogen Production with Different Biomass using Gasification routes.

Biomass	Reactor configuration	Catalyst	Operating conditions	H ₂ production (wt %)	Gas Yield (Nm ³ /kg _{biomass})	Tar content (g/Nm ³)	Ref.
Pine wood	Downdraft fixed bed	-	T = 850 °C	6.2	1.4	-	[70]
Waste wood	Fluidized bed	Silica sand	T = 900 °C S/B = 1	5.9	1.22	12.5	[71]
Wood pellets	Dual fluidized bed	Olivine	T = 815 °C S/B = 0.84	0.76	2.2	4.4	[71]
Pine wood pellets	Dual fluidized bed	Silica sand	T = 820 °C S/B = 2	1.8	0.82	10.3	[68]
Almond shells	Fluidized bed	Olivine : Dolomite (9:1)	T = 820 °C S/B = 0.72	7.3	1.58	2.13	[72]
Sewage sludge	Dual fluidized bed	Silica sand	T = 820 °C S/B = 1.5	3.6	0.85	122	[73]
Pine needles	Bubbling fluidized bed	CaO	T = 850 °C S/B = 1.6	12.4	1.98	-	[73]
Torrefied woodchips	Bubbling fluidized bed	-	T = 800-900 °C S/B = 0.32	1.12	0.89	-	[74]
Corn straw	Downdraft fixed bed	Blast furnace gas ash	T = 850 °C	5.6	3.01	-	[75]
Palm kernel shell	Fluidized bed	Ni powder	T = 750 °C S/B = 2	49 mol/kg	-	-	[76]
Beech wood	Cavity-type solar reactor	-	T = 1100-1300 °C S/B = 2	6.8	0.85	-	[77]
<i>Enteromorpha intestinalis</i> (algae)	Tubular batch reactor	Fe–Ni–Ru/γ-Al ₂ O ₃	T = 440 °C	12.28 mol/kg	30.16 mol/kg	-	[78]

3.1.2 Pyrolysis Technique

Pyrolysis is a process that thermally decomposes biomass in the absence of oxygen, resulting in the production of gases such as carbon dioxide, carbon monoxide, hydrogen, and methane, as well as solid char and fumes [74]. It offers benefits such as cost-effective process, easy storage and transportation, along with suitability for containers, appliances, turbines, and incinerators. It decomposes major macromolecules, such as cellulose, protein, carbohydrates, hemicellulose, and lipids, into simpler structures of vapours and gases. It can be grouped into fast pyrolysis (450-600 °C), slow pyrolysis (450 °C), and flash pyrolysis depending on the operating temperature [75]. The overall reaction involved is given by equation 4 [76].



The pyrolysis process includes complex primary and secondary reaction pathways. This is illustrated in Figure 11.




Figure 11: Mechanistic pathways of hydrogen formation during biomass pyrolysis.

In primary pyrolysis lignocellulosic biomass decomposes under heat. It produces char, condensable vapours (bio-oil) and non-condensable gases. These primary products subsequently participate in secondary reactions. Secondary reactions include thermal cracking and reforming. Hydrogen, carbon monoxide and carbon dioxide are produced as result. The final hydrogen yield and gas composition are strongly influenced by the extent of these secondary reactions. The working of pyrolysis reactor is presented in Figure 12.




Figure 12: Schematic Representation for Pyrolysis.

The process begins with drying the biomass, and then it is directed towards the pyrolysis unit. It is then sent to the cyclone separator, the combustion system, and finally the condenser. The combustion system burns off the remaining char, which is used during the drying process of biomass. The condenser yields gaseous products and bio-oils. These are then purified and separated into usable products and side products. Bio oil is a heterogeneous fluid similar to tar and can be categorised into water-soluble and insoluble fractions (olefins, xylene, toluene, and benzene). They consist of furan,

phenols, organic acids, alcohols, and ash. The characteristics of bio-oil are influenced by parameters of pyrolysis, the type of reactor, and the type of biomass employed. Some of the biomass is presented in table 3.

Table 3: Different Biomass used in Hydrogen Production via Pyrolysis.


Biomass	Reactor configuration	Catalyst	Operating conditions	H₂ production (wt %)	Ref.
Poplar wood/Pine	Fixed bed	Ni/Mg-Al with Ce	T = 650 °C	14.7	[84]
Pine sawdust	Fixed bed/Fluidized bed	Ni/La ₂ O ₃ -Al ₂ O ₃	T = 500 °C	7.0	[85]
Coconut shell	Fixed bed	Fe/Olivine	T = 800 °C	17.9	[86]
Corn cob	Fixed bed	Ce-Ni/Co-Al ₂ O ₃	T = 650-850 °C	11.7	[87]
Wood sawdust	Fixed bed	Nano Fe-Zn/Al ₂ O ₃	T = 500 °C	1.9	[88]
Wood sawdust	Fixed bed	Ni/CaAlO _x	T = 800 °C	3.1	[89]
Wood sawdust	Fixed bed	NiZnAlO _x	T = 535 °C	4.0	[90]
Wood sawdust	Fixed bed	Ca/Ni-Mg-AlO _x	T = 550 °C	4.3	[90]
Wood pellets	Fixed bed	Acid treated tyre char	T = 500 °C	6.1	[91]
Cellulose	Fixed bed	Ni/Al ₂ O ₃	T = 800 °C	5.9	[92]
Rice husk	Fixed bed	RHC Ni	T = 750°C	24.3 (vol %)	[93]
Corn cob	Fixed bed	Ni-lignite char	T = 900 °C	12.2	[94]
Corn cob	Fixed bed	Ni-exchanged resin char	T = 900 °C	12.3	[95]
Corn cob	Fixed bed	Limonite	T = 900 °C	14.8	[96]
Pine wood sawdust	Spouted bed/Fluidized bed	Ni/Al ₂ O ₃	-	11.0	[97]

It has several limitations, like poor heating value, high oxygen and moisture content, dense and viscous, and a strong corrosive nature [75]. These limitations cause chemical instability and deterioration during storage. Despite the drawbacks, it is a promising alternative for producing hydrogen. Pyrolysis of biomass has been shown to enhance energy recovery during hydrogen production [78, 79].

3.2 Biochemical route

3.2.1 Dark fermentation

Dark fermentation begins when economical anaerobic microbes (obligatory and facultative) are kept without light at operating temperatures over 25 °C [98]. Species of *Clostridium*, *Enterobacter*, *Bacteroides* and *Ruminococcus* are the most prevalent microbes used during the process [99,100]. The various gases produced based on the substrate being converted during the process are hydrogen, carbon dioxide, carbon monoxide, hydrogen sulphide, and methane. Catalysis of carbohydrates is the central process during this technique. Only a small amount of hydrogen is generated since other gases are also produced during the process [101,102]. It is necessary to implement an efficient method for isolating and purifying gases. The presence of by-products in the reaction further alters hydrogen production levels. With one mole of glucose, two moles and four moles of hydrogen are produced when butyric acid and acetic acid are the byproducts, respectively [103]. The overall reactions involved are presented in equations 5 and 6.



The microbial strain employed and the sugar content of the substrate influence the efficiency. Partial pressure of gas and pH are among other parameters that impact hydrogen generation [104]. Biomass-based hydrogen production by dark fermentation using different substrate with different parameters are presented in table 4 [107].


Table 4: Different substrate with hydrogen yield and other parameters via Dark Fermentation.

Substrate	pH	Temp (°C)	Microbe	Reactor	Hydrogen yield	Ref.
Washing wastewater from beverages	5.5	40	Mixed cultures (wastewater treatment plant)	-	0.30 mol/mol hexose	[108]
Food waste	-	36	Mixed culture from aerobic sludge	Batch	70.34 cm ³ /gVS	[109]
Raw cassava starch	-	35	Facultative anaerobic bacteria	Batch	1.44 mol/mol glucose	[110]
Pumpkin and potato waste	7.5	35	Anaerobic sludge	Batch	135.6 cm ³ /VS	[111]
Palm oil mill effluent	6.8	35	Mixed cultures	Upflow column bioreactor	0.52 mol/mol glycerol	[112]
<i>Jatropha curcas</i> (biodiesel industry residue)	5.5	37	Mixed cultures	Continuous stirred tank reactor	148 cm ³ /g carbohydrate 324 mmol/mol glycerol	[113]
Cassava starch wastewater	5.5	30	Mixed cultures	Batch	1.58 mol/mol hexose	[114]
Palm oil decanter cake with glycerin	7	55	Mixed cultures	Semi continuous	-	[115]
Barley hulls	-	60	<i>Clostridium thermocellum</i>	Batch	1.07 mmol/g substrate	[116]
Cornstalk	7.5	55	<i>Clostridium sartagoforme</i>	Batch	6.38 mmol/g substrate	[117]
Cornstalk	6.5	35	<i>Thermoanaerobacterium</i>	Batch	87.2 cm ³ /g substrate	[118]
Corn staw	6.5	37	<i>Ethanoligenes harbinense</i>	Batch	72 cm ³ /g	[119]
Rice husk	7	35	Mixed cultures (sewage sludge digester)	Batch	1.25 mol/mol substrate	[120]
Pine tree wood	7	35	Mixed cultures (sewage sludge digester)	Batch	0.99 mol/mol substrate	[120]
Cheese wey powder	-	55	Mixed cultures from sugarcane stillage T	-	3.67 mol/mol lactose	[121]

Biomass-derived sugars are converted to pyruvate through glycolysis. This generates ATP and reducing equivalents (NADH/ferredoxin). Pyruvate is subsequently transformed into acetyl-CoA. The electrons released during these reactions are utilized by hydrogenase enzymes to produce H₂. The metabolic fate of acetyl-CoA influences hydrogen yield. The acetate pathway produces higher H₂ yields than the butyrate pathway. Therefore, operating conditions favouring acetate formation are usually preferred for enhanced biohydrogen production.

3.2.2 Photo fermentation

Photo fermentation relies on the nitrogenase enzyme to generate hydrogen from biomass using light energy in a nitrogen-deprived medium. The overall reactions involved are given in equation 7.



Organic acids undergo conversion to hydrogen and carbon dioxide via photosynthesis by the action of non-sulphur purple anaerobic bacteria [122]. The most common bacterial strains involved are *Rhodobium*, *Rhodobacter*, *Rhodospirillum*, and *Rhodopseudomonas* [123]. Oxygen is not produced in these conversions as it inhibits the nitrogenase enzyme [124].

The photo-fermentation process involves the oxidation of organic acids through the tricarboxylic acid (TCA) cycle. Reducing equivalents are generated in the form of NADH. These electrons are transferred via ferredoxin to the nitrogenase enzyme. ATP required for the reaction is supplied by light-driven cyclic photophosphorylation in purple non-sulphur bacteria. Under nitrogen-limited conditions, nitrogenase utilizes

the reducing power and ATP. This reduces protons and produces hydrogen. Carbon dioxide is released during substrate oxidation, as is illustrated in Figure 14.






Figure 14: Flow chart for Photo-fermentation.


Mo-Nitrogenase



V-Nitrogenase



Fe-Nitrogenase



The process may follow either a single stage or a dual stage configuration. A single stage process setup is cost-effective to install but suffers from lower efficiencies [125].

The dual stage process uses dark fermentation beforehand to increase hydrogen

production by processing the organic acids generated first but this creates more complex operations. A peak hydrogen yield of 77.78 mL per litre per hour was reported for the photo-fermentation process [126]. The performance of this technique depends on preprocessing technique, bacterial engineering and configuration of the bioreactor. It is further affected by the choice of substrate, microbial species, and operational parameters [127]. The primary obstacle to industrial adoption of photo-fermentation is insufficient light intensity. Simply raising intensity of light does not solve the problem because excessive light hampers the growth of the bacteria and lower light conversion efficiency [128]. This issue is currently addressed by using shallow reactors to ensure that the substrate surface is exposed to the proper light [129].

Chapter 4

TECHNOLOGY ASSESSMENT AND ECONOMIC EVALUATION

Chapter 4

TECHNOLOGY ASSESSMENT AND ECONOMIC EVALUATION

4.1 Technology readiness level (TRL)

TRL assessment is a valuable method for identifying challenges and perspectives associated with technological innovation or new concepts [130]. It is a framework (level 1-9) that evaluates the maturity of a technology and allows a comparison between different technologies. Figure 15 represents the flow chart for TRL.




Figure 15: Flowchart for TRL.

Industries worldwide have implemented TRL evaluations. Moving from lower to higher TRLs transforms a conceptual idea into a practical technology that can function in real industrial environments [131,132]. Level 1 through 3 indicate lab-scale research, 4 through 6 indicate pilot-scale developments, and 7 through 9 indicate technologies ready for industrial deployment [133]. Pyrolysis is evidently the primary method used for large-scale hydrogen generation. Liquid and gaseous biomass pyrolysis technologies are at TRL 4, while solid biomass pyrolysis has progressed to TRL 8 and is suitable for commercial use. Gasification of biomass has progressed to TRL level 6. Photo fermentation and dark fermentation are still in their early stages and call for extensive scientific advancements [134]. Table 5 presents the technology for TRL.

Table 5: The technology and scale implement in TRL.

Technology	TRL	Scale	Efficiency (%)	Ref.
Gasification	4-7	Laboratory and bench scale	35-50	[135–137]
Pyrolysis	7	Bench	65	[135,138,139]
Dark fermentation	5	Laboratory scale	60-80	[59,123,137]
Photo fermentation	4	Laboratory scale	Light conversion efficiency 1-5	[59,123]

Technological maturity (TRL) and economic performance are important evaluation criteria. Along with these, environmental indicators like greenhouse gas emissions are assessed. This assessment enables a preliminary LCA-based comparison. The comparison focuses on different biomass-to-hydrogen conversion pathways.

4.2 Technoeconomic analysis (TEA)

A kinetic model was applied by Cook et al. to analyse the prospects of three separate biomass gasification units. The emission level in each plant fell between 2.92 and 3.15 kg of carbon dioxide per kg of hydrogen. Breakeven cost for hydrogen production fell between \$4.07-4.71 per kg of hydrogen in the absence of tax credits, while it fell between \$3.47-3.63 per kg of hydrogen in the presence of tax credits. Capital investment was identified as the dominant factor affecting hydrogen breakeven cost in the sensitivity results. It was further affected by the cost of the feedstock, length of the pipeline, and tax credits. Thus, these results show that the elements impose the strongest problem to scaling hydrogen gasification in industry [140].

Alam et al. in 2024 developed a process model in which wastewater sludge was used as the feedstock for dark fermentation. The production cost of hydrogen was \$11.4 per kg of hydrogen when the flow rate of feedstock was 23 tonnes per day. This cost reduced to \$5.9 per kg of hydrogen when the flow rate was increased to 500 tonnes per day. They also found that 17.5 kg of carbon dioxide was produced per kg of hydrogen. Capital investment and labour cost were identified as the dominant factors affecting hydrogen breakeven cost in the sensitivity results [141].

Genç et al. developed a process model in which dilute molasses was used as the feedstock for photo fermentation. The production cost of hydrogen was \$13.62 per kg of hydrogen when the production rate of hydrogen was 0.7 mmol per litre per hour. This resulted from the high costs of the cooling system and the bioreactor, making it economically nonviable. This suggests that research is needed to improve hydrogen

production by the photofermentation technique [142]. Table 6 presents the cost analysis of the techniques.

Table 6: Cost and efficiency for different hydrogen production technologies.

Technique	Cost (\$/kg)	CO ₂ Emission	H ₂ recovery efficiency (%)	Ref.
Gasification	2	15%/kg syngas	48	[132,143]
Pyrolysis	1.47	1.5 kg CO ₂ /kg H ₂	42.5	[144]
Dark fermentation	2.57	47%/kg H ₂	22.5	[145]

The combined evaluation of TRL, techno-economic indicators and environmental emissions provide an integrated framework for assessing the sustainability of biomass-based hydrogen production technologies. Thermochemical pathways like gasification and pyrolysis are more economically feasible for production of hydrogen. They also result in moderate levels of carbon emissions. In contrast, biochemical pathways such as dark and photo fermentation are less technologically mature. They are associated with higher costs and environmental impacts. It is therefore important to examine the readiness of the process in technologies for producing hydrogen from biomass. Economic feasibility must be considered at the same time. Moreover environmental performance should be part of the assessment. Only by considering all these aspects together can truly sustainable pathways be identified.

Chapter 5

CONCLUSION AND FUTURE SCOPE

Chapter 5

CONCLUSION AND FUTURE SCOPE

5.1 Merits and demerits of various techniques for the production of hydrogen from biomass

Various techniques were employed for the production of hydrogen production from biomass [123]. Table 7 represents merits and demerits for techniques.

Table 7: Merit and Demerit of several techniques.

Techniques	Merits	Demerits
Gasification	• Valorisation of industrial and forestry byproducts. • Adapt to existing industrial configuration • Eliminates the requirement for a costly oxygen supply • High productivity	• Carbon dioxide emission • Requires high temperatures (700-1000 °C) • Char and tar lead to deactivation of the catalyst • Reactor is costly
Pyrolysis	• Wide range biomass conversion (biochar, gas, bio-oil) • Uncomplicated method • Adapt to existing industrial configuration • Valorisation of industrial byproducts	• Carbon dioxide emission • Char and tar are produced • Catalyst needs to be regenerated • Reactor is costly
Dark fermentation	• Conversion of organic and biological waste into usable resources • Processes algal biomass • Requires mild pressures and temperatures	• Requirement of preprocessing • Low hydrogen production and low rate of yield • Byproducts are numerous
Photo fermentation	• Substrate conversion approaching completion • Conversion of organic and biological waste into usable resources • Requires mild pressures and temperatures	• Low hydrogen production and low rate of yield • Requirement of broad surface area • Requirement of bacteria • Requirement of high energy by the enzymes

-
- Light conversion efficiency is low
-

It is apparent that both thermochemical techniques (gasification and pyrolysis) lead to carbon dioxide emission during production of hydrogen. However, these techniques have many advantages. It is useful in valorisation of industrial and forestry products and adapts easily to existing industrial configuration [104]. These techniques lower the requirement for oxygen and have comparatively higher hydrogen production efficiencies. Fermentation techniques being relatively new methods still require more research to make it economically and commercially more viable [8].

5.2 Conclusion

As the world transitions toward low-carbon energy systems, this article highlights the increasing importance of biomass as a practical and sustainable feedstock for hydrogen production. Since biomass has inherent adaptability, a variety of conversion methods are available, which can be used to convert it, with thermochemical and biological processes. It is evident that lignocellulosic and organic leftovers offer a rich resource capable of sustaining large-scale hydrogen generation without competing with food systems when starting with the basics of biomass availability and features. It involves the thermochemical methods, such as gasification and pyrolysis, which exhibit high conversion efficiency and comparatively advanced Technology Readiness Levels (TRLs), making them more feasible for commercial application. It covers preprocessing techniques and conversion pathways. Conversion routes include thermochemical and biological routes. It also includes TRL, a techno-economic

assessment, and an evaluation of the merits of the biomass-based reactor for hydrogen production.

Overall, biomass-derived hydrogen is a viable alternative to fossil fuel-based production. It has potential for future clean energy systems. However, it faces many challenges regarding efficiency, scalability, and economics.

5.3 Future Scope

Even though significant progress in hydrogen production technologies several challenges still remain. These challenges include process efficiency, feedstock variability, scalability and economic viability. Future research should focus on the development of advanced catalysts. Integration of pretreatment and conversion systems along with process optimization should be the key focus. Techniques should be developed for integration of carbon capture. Improvements are necessary in reactor design as well as in feedstock logistics. Policy support mechanisms will be essential for accelerating commercialization. Additionally, hybrid thermochemical-biochemical approaches offer promising opportunities for hydrogen production. Further waste biomass utilization can improve the economic viability of hydrogen production.

References

- [1] U. Bello, H. Adamu, S. Samsuri, M. Qamar, Bibliometric analysis and road-mapping on hydrogen production from biomass-derived glycerol, *Int. J. Hydrogen Energy* 117 (2025) 353–373.
<https://doi.org/10.1016/j.ijhydene.2025.03.095>.
- [2] S. Kafle, S. Sapkota, B.T. Higgins, S. Adhikari, Research trends in life cycle assessment of hydrogen production: Methodological review on thermochemical conversion processes, *Int. J. Hydrogen Energy* 106 (2025) 432–443. <https://doi.org/10.1016/j.ijhydene.2025.01.472>.
- [3] S. Bakhsh, W. Zhang, K. Ali, Strategy towards sustainable energy transition: The effect of environmental governance, economic complexity and geopolitics, *Energy Strateg. Rev.* 52 (2024) 101330.
<https://doi.org/10.1016/j.esr.2024.101330>.
- [4] S. Ehsan, M.A. Wahid, Hydrogen production from renewable and sustainable energy resources : Promising green energy carrier for clean development, *Renew. Sustain. Energy Rev.* 57 (2016) 850–866.
<https://doi.org/10.1016/j.rser.2015.12.112>.
- [5] A.G. Olabi, K. Elsaid, K. Obaideen, M. Ali, Renewable energy systems: Comparisons, challenges and barriers, sustainability indicators, and the contribution to UN sustainable development goals, *Int. J. Thermofluids* 20 (2023) 100498. <https://doi.org/10.1016/j.ijft.2023.100498>.

- [6] M. Santamouris, K. Vasilakopoulou, Present and future energy consumption of buildings : Challenges and opportunities towards decarbonisation, E-Prime - Adv. Electr. Eng. Electron. Energy 1 (2021) 100002.
<https://doi.org/10.1016/j.prime.2021.100002>.
- [7] Pedigree, Wheat Straw, Idaho Natl. Lab. (2015) 2014–2016.
- [8] M. Ikhsan, K. Viswanathan, W. Wu, N. Hattu, A.E. Atabani, A critical review of the hydrogen production from biomass-based feedstocks : Challenge , solution , and future prospect, Process Saf. Environ. Prot. 164 (2022) 384–407. <https://doi.org/10.1016/j.psep.2022.06.006>.
- [9] L. Cao, I.K.M. Yu, X. Xiong, D.C.W. Tsang, S. Zhang, J.H. Clark, C. Hu, Y. Hau, J. Shang, Y. Sik, Biorenewable hydrogen production through biomass gasification : A review and future prospects, Environ. Res. 186 (2020) 109547. <https://doi.org/10.1016/j.envres.2020.109547>.
- [10] M.A. Elazab, A.T. Elgohr, M. Bassyouni, A.E. Kabeel, M.E.H. Attia, M.K. Elshaarawy, A.K. Hamed, H.A.H. Alzahrani, Green Hydrogen: Unleashing the Potential for Sustainable Energy Generation, Results Eng. 27 (2025) 106031. <https://doi.org/10.1016/j.rineng.2025.106031>.
- [11] Ł. Rafa, I. Ho, K. Kucharska, M. Glinka, P. Rybarczyk, Hydrogen production from biomass using dark fermentation, Renew. Sustain. Energy Rev. 91 (2018) 665–694. <https://doi.org/10.1016/j.rser.2018.04.043>.
- [12] M.H. Bhuiyan, Z. Siddique, Hydrogen as an alternative fuel : A comprehensive review of challenges and opportunities in production , storage , and transportation, Int. J. Hydrogen Energy 102 (2025) 1026–1044.
<https://doi.org/10.1016/j.ijhydene.2025.01.033>.

- [13] H. Cheikhvat, N. Chaumeix, A. Bentaib, C. Paillard, Flammability Limits of Hydrogen-Air Mixtures, *Nucl. Technol.* 178 (2018) 5-16.
<https://doi.org/10.13182/NT12-A13543>.
- [14] M. Usman, S. Akhtar, F. Asfand, A. Shabruhi, R. Mishra, M.I. Khan, Hydrogen as a sustainable combustion fuel : Performance , challenges , and pathways for transition to low-carbon propulsion systems, *Renew. Sustain. Energy Rev.* 223 (2025) 116004. <https://doi.org/10.1016/j.rser.2025.116004>.
- [15] I. Rolo, V.A. F. Costa, F.P. Brito, Hydrogen-Based Energy Systems: Current Technology Development Status, Opportunities and Challenges, *Energies* 17 (2024) 180. <https://doi.org/10.3390/en17010180>.
- [16] A.M. Sadeq, R.Z. Homod, A. Kadhim, H. Togun, A. Mahmoodi, H.F. Isleem, A.R. Patil, A. Hedayati, Hydrogen energy systems : Technologies , trends , and future prospects, *Sci. Total Environ.* 939 (2024) 173622.
<https://doi.org/10.1016/j.scitotenv.2024.173622>.
- [17] M. Amin, H. Hussain, A. Gul, W. Ullah, E. Chung, A. Zia, Z. Ur, R. Farooqi, C. Lee, Hydrogen production through renewable and non- renewable energy processes and their impact on climate change, *Int. J. Hydrogen Energy* 47 (2022) 33112–33134. <https://doi.org/10.1016/j.ijhydene.2022.07.172>.
- [18] J. Juan, B. Caballero, I.N. Zaini, W. Yang, Reforming processes for syngas production: A mini-review on the current status, challenges, and prospects for biomass conversion to fuels, *Appl. Energy Combust. Sci.* 10 (2022) 100064.
<https://doi.org/10.1016/j.jaecs.2022.100064>.
- [19] D. Johnravindar, R. Selvakumar, Applications of Green Hydrogen with Commercial Feasibility : Identifying Gaps , Perspectives , and Bottlenecks,

- American Chemical Society, 2024. <https://doi.org/10.1021/bk-2024-1474.ch001>.
- [20] M. Salom, E. Kraveva, H. Ehrich, N.A. Uriarte, R. Sanz, D. Alique, M.A. Soria, L.M. Madeira, High-purity H₂ production through glycerol steam reforming in multifunctional reactors, *Chem. Eng. J.* 505 (2025) 159230. <https://doi.org/10.1016/j.cej.2025.159230>.
- [21] T. Lepage, M. Kammoun, Q. Schmetz, A. Richel, Biomass-to-hydrogen: A review of main routes production, processes evaluation and techno-economical assessment, *Biomass and Bioenergy* 144 (2021) 105920. <https://doi.org/10.1016/j.biombioe.2020.105920>.
- [22] J. Wang, W. Wan, Factors influencing fermentative hydrogen production : A review, *Int. J. Hydrogen Energy* 34 (2009) 799–811. <https://doi.org/10.1016/j.ijhydene.2008.11.015>.
- [23] Y. Wang, J.J. Wu, Thermochemical conversion of biomass : Potential future prospects, *Renew. Sustain. Energy Rev.* 187 (2023) 113754. <https://doi.org/10.1016/j.rser.2023.113754>.
- [24] P. Chowdhury, N.A. Mahi, R. Yeassin, N. Chowdhury, O. Farrok, Energy Conversion and Management : X Biomass to biofuel : Impacts and mitigation of environmental , health , and socioeconomic challenges ☆, *Energy Convers. Manag. X* 25 (2025) 100889. <https://doi.org/10.1016/j.ecmx.2025.100889>.
- [25] K. Parmar, Biomass- An Overview on Composition Characteristics and Properties, *IRA-International J. Appl. Sci.* (ISSN 2455-4499) 7 (2017) 42. <https://doi.org/10.21013/jas.v7.n1.p4>.
- [26] N.K. Obiora, C.O. Ujah, C.O. Asadu, F.O. Kolawole, B.N. Ekwueme,

- Production of hydrogen energy from biomass: Prospects and challenges,
Green Technol. Sustain. 2 (2024) 100100.
<https://doi.org/10.1016/j.grets.2024.100100>.
- [27] S. Ishola, I. Michael, S. Anekwe, S. Okiemute, K. Bab, E. Kweinor, A. Samaila, Y. Makarfi, Biomass conversion for sustainable hydrogen generation : A comprehensive review, Fuel Process. Technol. 272 (2025) 108210. <https://doi.org/10.1016/j.fuproc.2025.108210>.
- [28] P. Khunnonkwao, S. Thitiprasert, P. Jaiaue, The outlooks and key challenges in renewable biomass feedstock utilization for value-added platform chemical via bioprocesses, Heliyon 10 (2024) e30830.
<https://doi.org/10.1016/j.heliyon.2024.e30830>.
- [29] T. Prince, C. Ezeorba, E. Sunday, M. Habila, C. Ogugua, T. Christian, Reports Recent advances in biotechnological valorization of agro-food wastes (AFW): Optimizing integrated approaches for sustainable biorefinery and circular bioeconomy, Bioresour. Technol. Reports 26 (2024) 101823.
<https://doi.org/10.1016/j.biteb.2024.101823>.
- [30] A. Saravanan, P.S. Kumar, N.S. Mat Aron, S. Jeevanantham, S. Karishma, P.R. Yaashikaa, K.W. Chew, P.L. Show, A review on bioconversion processes for hydrogen production from agro-industrial residues, Int. J. Hydrogen Energy 47 (2022) 37302–37320.
<https://doi.org/10.1016/j.ijhydene.2021.08.055>.
- [31] M. Zieli, Agricultural Wastes and Their By-Products for the Energy Market, Energies 17 (2024) 2099. <https://doi.org/10.3390/en17092099>.
- [32] L.C. Energy, R. Technologies, A. Materials, A. Parthiban, S. Korea, S.

- National, S. Korea, G.C. Umenweke, U. Musa, L.C. Energy, R. Technologies, P.E. Technology, O. Williams, A. Materials, Y. Mortezaei, E. Science, M. Pleasant, S. Korea, S. Korea, E. Lester, A. Materials, C.C. Ogbaga, I. Researcher, N. Yorkshire, B. Gunes, J.A. Okolie, Progress in lignocellulosic biomass valorization for biofuels in the EU : A focus on thermochemical, Biofuels Bioprod. Biorefining 18 (2024) 755–781.
<https://doi.org/10.1002/bbb.2544>.
- [33] G. Kumar, P. Bakonyi, S. Periyasamy, S.H. Kim, N. Nemestóthy, K. Béla, Lignocellulose biohydrogen : Practical challenges and recent progress, Renew. Sustain. Energy Rev. 44 (2015) 728–737.
<https://doi.org/10.1016/j.rser.2015.01.042>.
- [34] C.L. Williams, T.L. Westover, R.M. Emerson, Sources of Biomass Feedstock Variability and the Potential Impact on Biofuels Production, Bioenergy Res. 9 (2016) 1–14. <https://doi.org/10.1007/s12155-015-9694-y>.
- [35] P.K. Rai, Recent Advances in substrate utilization for fermentative hydrogen Production, J. Appl. Biol. Biotechnol. 4 (2016) 59–67.
<https://doi.org/10.7324/JABB.2016.40608>.
- [36] P.R. Yaashikaa, M. Keerthana Devi, P. Senthil Kumar, G. Rangasamy, S. Rajendran, L. Xiao, A review on pretreatment methods, photobioreactor design and metabolic engineering approaches of algal biomass for enhanced biohydrogen production, Int. J. Hydrogen Energy 48 (2023) 21110–21127.
<https://doi.org/10.1016/j.ijhydene.2022.10.092>.
- [37] D. Nagarajan, J. Chang, D. Lee, Pretreatment of microalgal biomass for efficient biohydrogen production – Recent insights and future perspectives,

- Bioresour. Technol. 302 (2020) 122871.
<https://doi.org/10.1016/j.biortech.2020.122871>.
- [38] P.K. Rai, S.P. Singh, Integrated dark- and photo-fermentation: Recent advances and provisions for improvement, *Int. J. Hydrogen Energy* 41 (2016) 1–15. <https://doi.org/10.1016/j.ijhydene.2016.08.084>.
- [39] K. Kucharska, P. Rybarczyk, I. Hołowacz, R. Łukajtis, Pretreatment of Lignocellulosic Materials as Substrates for Fermentation Processes, *Molecules* 23 (2018) 1–32. <https://doi.org/10.3390/molecules23112937>.
- [40] N. Chaitanya, D. Sivaramakrishna, B. Satish, V. Himabindu, M. Lakshminarasu, M. Vishwanadham, Selection of pretreatment method for enriching hydrogen-producing bacteria using anaerobic sewage sludge with three different substrates., *Biofuels* 7 (2016) 163-171.
<https://doi.org/10.1080/17597269.2015.1123969>.
- [41] C. Dixon, L.R. Wilken, Green microalgae biomolecule separations and recovery, *Bioresour. Bioprocess.* 5 (2018). <https://doi.org/10.1186/s40643-018-0199-3>.
- [42] Y. Yin, J. Hu, J. Wang, Enriching hydrogen-producing bacteria from digested sludge by different pretreatment methods, *Int. J. Hydrogen Energy* 39 (2014) 13550-13556. <https://doi.org/10.1016/j.ijhydene.2014.01.145>.
- [43] B. Rashidi, A. Dechesne, M.G. Rydahl, B. Jørgensen, L.M. Trindade, *Neochloris oleoabundans* cell walls have an altered composition when cultivated under different growing conditions, *Algal Res.* 40 (2019) 101482.
<https://doi.org/10.1016/j.algal.2019.101482>.
- [44] R. Rafieenia, F. Girotto, W. Peng, R. Cossu, A. Pivato, R. Raga, M.C.

- Lavagnolo, Effect of aerobic pre-treatment on hydrogen and methane production in a two-stage anaerobic digestion process using food waste with different compositions, *Waste Manag.* 59 (2016) 194-199.
<https://doi.org/10.1016/j.wasman.2016.10.028>.
- [45] P. Alvira, M. Ballesteros, M.J. Negro, Pretreatment technologies for an efficient bioethanol production process based on enzymatic hydrolysis : A review, *Bioresour. Technol.* 101 (2010) 4851–4861.
<https://doi.org/10.1016/j.biortech.2009.11.093>.
- [46] S. Haridoss, Studies on Biohydrogen production from rice mill waste water using *Enterobacter aerogenes* (MTCC 2822) by dark fermentation process, *J. Pet. Environ. Biotechnol.* 7 (2016) 10–13. <https://doi.org/10.4172/2157-7463.1000312>.
- [47] G. Kumar, G. Zhen, P. Sivagurunathan, P. Bakonyi, N. Nemestóthy, T. Kobayashi, K. Xu, Biogenic H₂ production from mixed microalgae biomass : impact of pH control and methanogenic inhibitor (BESA) addition, *Biofuel Res. J.* 11 (2016) 470–474. <https://doi.org/10.18331/BRJ2016.3.3.6>.
- [48] W. Kenealy, J.G. Zeikus, Influence of Corrinoid Antagonists on Methanogen Metabolism, *J. Bacteriol.* 146 (1981) 133–140.
<https://doi.org/10.1128/jb.146.1.133-140.1981>.
- [49] A. Chidthaisong, R. Conrad, Specificity of chloroform , 2-bromoethanesulfonate and ⁻uoroacetate to inhibit methanogenesis and other anaerobic processes in anoxic rice field soil, *Soil Biol. Biochem.* 32 (2000) 977–988.
- [50] S.K. Khanal, *Anaerobic Biotechnology for Bioenergy Production Principles*

and Applications, Blackwell Publishing, 2008.

- [51] Z. Tiantao, Z. Lijie, C. Haoquan, Z. Youcai, Co-inhibition of methanogens for methane mitigation in biodegradable wastes, *J. Environ. Sci.* 21 (2009) 827–833. [https://doi.org/10.1016/S1001-0742\(08\)62348-7](https://doi.org/10.1016/S1001-0742(08)62348-7).
- [52] M. V Bule, A.H. Gao, B. Hiscox, S. Chen, Structural Modification of Lignin and Characterization of Pretreated Wheat Straw by Ozonation, *J. Agric. Food Chem.* 61 (2013) 3916–3925.
- [53] S. Sreevathsan, I. Crasta, B.K. Bhavana, Effect of ozonation on biodegradability enhancement and biomethanation potential of pretreatment process wastewaters from 2G ethanol production, *J. Chem. Technol. Biotechnol.* (2023) 1425–1434. <https://doi.org/10.1002/jctb.7361>.
- [54] V.C. Deivayanai, P.R. Yaashikaa, P. Senthil Kumar, G. Rangasamy, A comprehensive review on the biological conversion of lignocellulosic biomass into hydrogen: Pretreatment strategy, technology advances and perspectives, *Bioresour. Technol.* 365 (2022) 128166. <https://doi.org/10.1016/j.biortech.2022.128166>.
- [55] C. Sánchez, Lignocellulosic residues : Biodegradation and bioconversion by fungi, *Biotechnol. Adv.* 27 (2009) 185–194. <https://doi.org/10.1016/j.biotechadv.2008.11.001>.
- [56] M. Shamsi, A. Abbas, S. Farokhi, A. Bayat, A novel process simulation model for hydrogen production via reforming of biomass gasification tar, *Int. J. Hydrogen Energy* 47 (2021) 772–781. <https://doi.org/10.1016/j.ijhydene.2021.10.055>.
- [57] B. Li, C. Fabrice, M. Mbeugang, D. Liu, S. Zhang, S. Wang, Q. Wang, Z. Xu,

- X. Hu, Simulation of sorption enhanced staged gasification of biomass for hydrogen production in the presence of calcium oxide, *Int. J. Hydrogen Energy* 45 (2020) 26855–26864.
<https://doi.org/10.1016/j.ijhydene.2020.07.121>.
- [58] S. Zou, Y. Wu, M. Yang, J. Tong, Bio-oil production from sub- and supercritical water liquefaction of microalgae *Dunaliella tertiolecta* and related properties, *Energy Environ. Sci.* 3 (2010) 1073–1078.
<https://doi.org/10.1039/c002550j>.
- [59] M. Ni, D.Y.C. Leung, M.K.H. Leung, K. Sumathy, An overview of hydrogen production from biomass, *Fuel Process. Tech* 87 (2006) 461–472.
<https://doi.org/10.1016/j.fuproc.2005.11.003>.
- [60] S. Ying, R. Keey, C. Leing, W. Peng, W. Peng, C. Sonne, Y. Fai, S. Shiung, Strategic hazard mitigation of waste furniture boards via pyrolysis: Pyrolysis behavior, mechanisms, and value-added products, *J. Hazard. Mater.* 421 (2022) 126774. <https://doi.org/10.1016/j.jhazmat.2021.126774>.
- [61] R.L. Reaño, A. Halog Analysis of carbon footprint and energy performance of biohydrogen production through gasification of different waste agricultural biomass from the Philippines, *Biomass Convers. Biorefinery* 13 (2023) 8685–8699. <https://doi.org/10.1007/s13399-020-01151-9>.
- [62] K. Dulta, A.O. Adeola, S.E. Ashaolu, T.I. Banji, J.O. Ighalo, Biohydrogen production and its bioeconomic impact : a review, *Waste Dispos. Sustain. Energy* 4 (2022) 231–242. <https://doi.org/10.1007/s42768-022-00109-z>.
- [63] A.N. Rollinson, 2016 Gasification reactor engineering approach to understanding the formation of biochar properties, *R. Soc.* 472 (2192)

20150841. <https://doi.org/10.1098/rspa.2015.0841>

- [64] F. Sher, S. Hameed, N.S. Omerbegović, A. Chupin, I.U. Hai, B. Wang, Y.H. Teoh, M.J. Yildiz, Cutting-edge biomass gasification technologies for renewable energy generation and achieving net zero emissions, *Energy Conversion and Management*. 323 (2025) 119213. <https://doi.org/10.1016/j.enconman.2024.119213>.
- [65] C. Xu, S. Chen, A. Soomro, Z. Sun, W. Xiang, Hydrogen rich syngas production from biomass gasification using synthesized Fe / CaO active catalysts, *J. Energy Inst.* (2017) 1–12. <https://doi.org/10.1016/j.joei.2017.10.014>.
- [66] X. Li, J. Grace, J.C. Lim, P. Watkinson, Biomass gasification in a circulating fluidized bed, *Biomass and Bioenergy* 26 (2004) 171–193. [https://doi.org/10.1016/S0961-9534\(03\)00084-9](https://doi.org/10.1016/S0961-9534(03)00084-9).
- [67] Z. Wang, T. He, J. Qin, J. Wu, J. Li, Z. Zi, G. Liu, J. Wu, L. Sun, Gasification of biomass with oxygen-enriched air in a pilot scale two-stage gasifier, *Fuel* 150 (2015) 386–393. <https://doi.org/10.1016/j.fuel.2015.02.056>.
- [68] Z. Zhang, S. Pang, Experimental investigation of biomass devolatilization in steam gasification in a dual fluidised bed gasifier, *Fuel* 188 (2017) 628–635. <https://doi.org/10.1016/j.fuel.2016.10.074>.
- [69] M. Ahmed, S.S. Malhotra, O. Yadav, Monika, C. Saini, N. Sharma, M.K. Gupta, R.K. Mohapatra, A. Ansari, DFT and TDDFT exploration on electronic transitions and bonding aspect of DPA and PTDC ligated transition metal complexes, *J. Mol. Model.* 30 (2024). <https://doi.org/10.1007/s00894-024-05912-5>.

- [70] Y. Niu, F. Han, Y. Chen, Y. Lyu, L. Wang, Experimental study on steam gasification of pine particles for hydrogen-rich gas, *J. Energy Inst.* (2016) 1–10.
<https://doi.org/10.1016/j.joei.2016.07.006>.
- [71] T.B. Vilches, J. Marinković, M. Seemann, H. Thunman, Comparing active bed materials in a dual fluidized bed biomass gasifier: olivine, bauxite, quartz-sand and ilmenite, *Energy Fuels*. 30 (2016) 4848–4857.
<https://doi.org/10.1021/acs.energyfuels.6b00327>.
- [72] S. Rapagnà, K. Gallucci, P. Ugo, Olivine , dolomite and ceramic filters in one vessel to produce clean gas from biomass, *Waste Manag.* 71 (2018) 792–800.
<https://doi.org/10.1016/j.wasman.2017.07.038>.
- [73] D. Schweitzer, A. Gredinger, M. Schmid, G. Waizmann, M. Beirow, G. Scheffknecht, R. Sp, Steam gasification of wood pellets , sewage sludge and manure : Gasification performance and concentration of impurities, *Biomass and Bioenergy* 111 (2018) 308–319.
<https://doi.org/10.1016/j.biombioe.2017.02.002>.
- [74] P. Kumari, Hydrogen-rich gas production with CO₂ capture from steam gasification of pine needle using calcium oxide : Experimental and modeling study, *Int. J. Energy Res.* 44 (2020) 6927–6938.
<https://doi.org/10.1002/er.5455>.
- [75] Y. Pang, D. Yu, Y. Chen, G. Jin, Hydrogen production from steam gasification of corn straw catalyzed by blast furnace gas ash, *Int. J. Hydrogen Energy* 45 (2020) 17191–17199.
<https://doi.org/10.1016/j.ijhydene.2019.02.235>.
- [76] Z. Khan, M. Shahbaz, S. Ali, A. Taqvi, A. Alnouss, T. Al-ansari, U. Ahmed,

- Equilibrium modelling of steam gasification of PKS system and CO₂ sorption using CaO : A digitalized parametric and techno-economic analysis, Digit. Chem. Eng. 13 (2024) 100184. <https://doi.org/10.1016/j.dche.2024.100184>.
- [77] S. Chuayboon, S. Abanades, S. Rodat, Experimental analysis of continuous steam gasification of wood biomass for syngas production in a high-temperature particle-fed solar reactor, Chem. Eng. Process. Process Intensif. 125 (2018) 253–265. <https://doi.org/10.1016/j.cep.2018.02.004>.
- [78] F. Ni, O. Norouzi, F. Safari, S. Jafarian, A. Tavasoli, A. Karimi, Hydrothermal gasification performance of *Enteromorpha intestinalis* as an algal biomass for hydrogen-rich gas production using Ru promoted, Energy Convers. Manag. 141 (2016) 63–71. <https://doi.org/10.1016/j.enconman.2016.04.083>.
- [79] A. Bakhtyari, M.A. Makarem, M.R. Rahimpour, Hydrogen Production Through Pyrolysis, Encyclopedia of Sustainability Science and Technology. (2018). https://doi.org/10.1007/978-1-4939-2493-6_956-1
- [80] A.R.K. Gollakota, M. Reddy, M.D. Subramanyam, N. Kishore, A review on the upgradation techniques of pyrolysis oil, Renew. Sustain. Energy Rev. 58 (2016) 1543–1568. <https://doi.org/10.1016/j.rser.2015.12.180>.
- [81] H. Yang, R. Yan, H. Chen, D. Ho, D. Tee, C. Zheng, Pyrolysis of palm oil wastes for enhanced production of hydrogen rich gases, Fuel Process. Technol. 87 (2006) 935–942. <https://doi.org/10.1016/j.fuproc.2006.07.001>.
- [82] A.K. Vuppaladadiyam, S.S.V. Vuppaladadiyam, A. Awasthi, A. Sahoo, S. Rehman, K.K. Pant, S. Murugavelh, Q. Huang, E. Anthony, P. Fennel, S. Bhattacharya, S.Y. Leu, Biomass pyrolysis: A review on recent advancements and green hydrogen production, Bioresour. Technol. 364 (2022) 128087.

<https://doi.org/10.1016/j.biortech.2022.128087>.

- [83] A.K. Vuppaladadiyam, S.S. Varsha Vuppaladadiyam, V.S. Sikarwar, E. Ahmad, K.K. Pant, M. S, A. Pandey, S. Bhattacharya, A. Sarmah, S.Y. Leu, A critical review on biomass pyrolysis: Reaction mechanisms, process modeling and potential challenges, *J. Energy Inst.* 108 (2023) 101236. <https://doi.org/10.1016/j.joei.2023.101236>.
- [84] S. Iglesias-v, A. Remiro, G. Elordi, D. Alique, A.J. Santos-carballes, R. Sanz, A. Calles, J. Bilbao, A.G. Gayubo, Steam reforming of bio-oil stabilized with ethanol over a Ni / MgAl₂O₄ catalyst in a Pd-membrane reactor, *Catal. Today* 460 (2025) 115445. <https://doi.org/10.1016/j.cattod.2025.115445>.
- [85] B. Valle, B. Aramburu, M. Olazar, J. Bilbao, A.G. Gayubo, Steam reforming of raw bio-oil over Ni/La₂O₃ - α Al₂O₃ : Influence of temperature on product yields and catalyst deactivation, *Fuel* 216 (2018) 463–474. <https://doi.org/10.1016/j.fuel.2017.11.149>.
- [86] C. Quan, S. Xu, C. Zhou, Steam reforming of bio-oil from coconut shell pyrolysis over Fe/olivine catalyst, *Energy Convers. Manag.* 141 (2016) 40-47. <https://doi.org/10.1016/j.enconman.2016.04.024>.
- [87] H. Xie, Q. Yu, Z. Zuo, Z. Han, X. Yao, Q. Qin, Hydrogen production via sorption-enhanced catalytic steam reforming of bio-oil, *Int. J. Hydrogen Energy* 41 (2016) 2345–2353. <https://doi.org/10.1016/j.ijhydene.2015.12.156>.
- [88] F. Chen, C. Wu, L. Dong, F. Jin, P.T. Williams, J. Huang, Catalytic steam reforming of volatiles released via pyrolysis of wood sawdust for hydrogen-rich gas production on Fe – Zn/Al₂O₃ nanocatalysts, *Fuel* 158 (2015) 999–1005. <https://doi.org/10.1016/j.fuel.2015.05.040>.

- [89] F. Chen, C. Wu, L. Dong, A. Vassallo, P.T. Williams, Characteristics and catalytic properties of Ni / CaAlOx catalyst for hydrogen-enriched syngas production from pyrolysis-steam reforming of biomass sawdust, "Applied Catal. B, Environ. 183 (2016) 168–175.
<https://doi.org/10.1016/j.apcatb.2015.10.028>.
- [90] F. Jin, H. Sun, C. Wu, H. Ling, Y. Jiang, P.T. Williams, Effect of calcium addition on Mg-AlOx supported Ni catalysts for hydrogen production from pyrolysis-gasification of biomass, Catal. Today 309 (2018) 2–10.
<https://doi.org/10.1016/j.cattod.2018.01.004>.
- [91] A.S. Al-rahbi, P.T. Williams, Hydrogen-rich syngas production and tar removal from biomass gasification using sacrificial tyre pyrolysis char, Appl. Energy 190 (2017) 501–509. <https://doi.org/10.1016/j.apenergy.2016.12.099>.
- [92] J. Zou, H. Yang, Z. Zeng, C. Wu, P.T. Williams, H. Chen, Hydrogen production from pyrolysis catalytic reforming of cellulose in the presence of K alkali metal, Int. J. Hydrogen Energy 41 (2016) 10598–10607.
<https://doi.org/10.1016/j.ijhydene.2016.04.207>.
- [93] Y. Shen, M. Chen, T. Sun, J. Jia, Catalytic reforming of pyrolysis tar over metallic nickel nanoparticles embedded in pyrochar, Fuel 159 (2015) 570–579. <https://doi.org/10.1016/j.fuel.2015.07.007>.
- [94] B. Wang, J. Cao, X. Zhao, Y. Bian, C. Song, Y. Zhao, X. Fan, X. Wei, T. Takarada, Preparation of nickel-loaded on lignite char for catalytic gasification of biomass, Fuel Process. Technol. 136 (2015) 17–24.
<https://doi.org/10.1016/j.fuproc.2014.07.024>.
- [95] J. Cao, T. Liu, J. Ren, X. Zhao, Y. Wu, J. Wang, X. Ren, X. Wei, Preparation

- and characterization of nickel loaded on resin char as tar reforming catalyst for biomass gasification, *J. Anal. Appl. Pyrolysis* 127 (2017) 82–90.
<https://doi.org/10.1016/j.jaap.2017.08.020>.
- [96] X. Zhao, J. Ren, J. Cao, F. Wei, C. Zhu, X. Fan, Y. Zhao, X. Wei, Catalytic reforming of volatiles from biomass pyrolysis for hydrogen-rich gas production over limonite ore, *Energy and Fuels* 31 (2017) 4054–4060.
<https://doi.org/10.1021/acs.energyfuels.7b00005>.
- [97] A. Arregi, G. Lopez, M. Amutio, I. Barbarias, J. Bilbao, M. Olazar, Hydrogen production from biomass by continuous fast pyrolysis and in-line steam reforming, *RSC Adv.* 6 (2016) 25975–25985.
<https://doi.org/10.1039/c6ra01657j>.
- [98] J.L. Varanasi, R. Veerubhotla, S. Pandit, D. Das, Biohydrogen production using microbial electrolysis cell: Recent advances and future prospects, *Biomass, Biofuels, Biochemicals*. 2018. <https://doi.org/10.1016/B978-0-444-64052-9.00035-2>.
- [99] E.L.N. Dzulkarnain, J.O. Audu, W.R.Z. Wan Dagang, M.F. Abdul-Wahab, Microbiomes of biohydrogen production from dark fermentation of industrial wastes: current trends, advanced tools and future outlook, *Bioresour. Bioprocess.* 9 (2022). <https://doi.org/10.1186/s40643-022-00504-8>.
- [100] H. Singh, S. Tomar, K.A. Qureshi, M. Jaremko, P.K. Rai, Recent Advances in Biomass Pretreatment Technologies for Biohydrogen Production, *Energies* 15 (2022) 999. <https://doi.org/10.3390/en15030999>
- [101] D. Talapko, J. Talapko, I. Erić, I. Škrlec, Biological Hydrogen Production from Biowaste Using Dark Fermentation, Storage and Transportation,

- Energies 16 (2023) 1–16. <https://doi.org/10.3390/en16083321>.
- [102] D.B. Levin, L. Pitt, M. Love, Biohydrogen production: Prospects and limitations to practical application, *Int. J. Hydrogen Energy* 29 (2004) 173–185. [https://doi.org/10.1016/S0360-3199\(03\)00094-6](https://doi.org/10.1016/S0360-3199(03)00094-6).
- [103] F.R. Hawkes, R. Dinsdale, D.L. Hawkes, I. Hussy, Sustainable fermentative hydrogen production: Challenges for process optimisation, *Int. J. Hydrogen Energy* 27 (2002) 1339–1347. [https://doi.org/10.1016/S0360-3199\(02\)00090-3](https://doi.org/10.1016/S0360-3199(02)00090-3).
- [104] S. Singh, G. Pandey, G.K. Rath, H.P. Veluswamy, N. Molokitina, Life cycle assessment of biomass-based hydrogen production technologies: A review, *Int. J. Green Energy* 22 (2023) 1454–1469. <https://doi.org/10.1080/15435075.2023.2245453>.
- [105] S. Eker, M. Sarp, Hydrogen gas production from waste paper by dark fermentation: Effects of initial substrate and biomass concentrations, *Int. J. Hydrogen Energy* 42 (2017) 2562–2568. <https://doi.org/10.1016/j.ijhydene.2016.04.020>.
- [106] E. Tapia-Venegas, J.E. Ramirez-Morales, F. Silva-Illanes, J. Toledo-Alarcón, F. Paillet, R. Escudie, C.H. Lay, C.Y. Chu, H.J. Leu, A. Marone, C.Y. Lin, D.H. Kim, E. Trably, G. Ruiz-Filippi, Biohydrogen production by dark fermentation: scaling-up and technologies integration for a sustainable system, *Rev. Environ. Sci. Biotechnol.* 14 (2015) 761–785. <https://doi.org/10.1007/s11157-015-9383-5>.
- [107] G. Kumar, S. Shobana, D. Nagarajan, D.J. Lee, K.S. Lee, C.Y. Lin, C.Y. Chen, J.S. Chang, Biomass based hydrogen production by dark fermentation

- recent trends and opportunities for greener processes, *Curr. Opin. Biotechnol.* 50 (2018) 136–145. <https://doi.org/10.1016/j.copbio.2017.12.024>.
- [108] C.M. Liu, J.L. Zheng, S.Y. Wu, C.Y. Chu, Fermentative hydrogen production potential from washing wastewater of beverage production process, *Int. J. Hydrogen Energy* 41 (2016) 4466–4473. <https://doi.org/10.1016/j.ijhydene.2015.08.079>.
- [109] L. Alibardi, R. Cossu, Composition variability of the organic fraction of municipal solid waste and effects on hydrogen and methane production potentials, *Waste Manag.* 36 (2015) 147–155. <https://doi.org/10.1016/j.wasman.2014.11.019>.
- [110] S. Wang, Z. Ma, T. Zhang, M. Bao, H. Su, Optimization and modeling of biohydrogen production by mixed bacterial cultures from raw cassava starch, *Front. Chem. Sci. Eng.* 11 (2017) 100–106. <https://doi.org/10.1007/s11705-017-1617-3>.
- [111] A. Ghimire, L. Frunzo, L. Pontoni, G. d'Antonio, P.N.L. Lens, G. Esposito, F. Pirozzi, Dark fermentation of complex waste biomass for biohydrogen production by pretreated thermophilic anaerobic digestate, *J. Environ. Manage.* 152 (2015) 43–48. <https://doi.org/10.1016/j.jenvman.2014.12.049>.
- [112] A.S. Dounavis, I. Ntaikou, G. Lyberatos, Production of biohydrogen from crude glycerol in an upflow column bioreactor, *Bioresour. Technol.* 198 (2015) 701–708. <https://doi.org/10.1016/j.biortech.2015.09.072>.
- [113] L.J. Martínez-Mendoza, O. García-Depraect, R. Muñoz, Unlocking the high-rate continuous performance of fermentative hydrogen bioproduction from fruit and vegetable residues by modulating hydraulic retention time,

- Bioresour. Technol. 373 (2023) 1–32.
<https://doi.org/10.1016/j.biortech.2023.128716>.
- [114] S. Sittijunda, S. Pattra, Evaluation of different pretreatment methods to prepare an inoculum for bio-hydrogen production from cassava starch wastewater, *KKU Res. J* 21 (2016) 81–92.
<https://doi.org/10.14456/kkurj.2016.22>.
- [115] S. Kanchanasuta, K. Kittipongpattana, N. Pisutpaisal, Improvement of biohydrogen fermentation by co-digestion of crude glycerol with palm oil decanter cake, *Chem. Eng. Trans.* 57 (2017) 1963–1968.
<https://doi.org/10.3303/CET1757328>.
- [116] N.Q. Ren, L. Zhao, C. Chen, W.Q. Guo, G.L. Cao, A review on bioconversion of lignocellulosic biomass to H₂: Key challenges and new insights, *Bioresour. Technol.* 215 (2016) 92–99. <https://doi.org/10.1016/j.biortech.2016.03.124>.
- [117] T. Sheng, L. Gao, L. Zhao, W. Liu, A. Wang, Direct hydrogen production from lignocellulose by the newly isolated *Thermoanaerobacterium thermosaccharolyticum* strain DD32, *RSC Adv.* 5 (2015) 99781–99788.
<https://doi.org/10.1039/c5ra20000h>.
- [118] J.N. Zhang, Y.H. Li, H.Q. Zheng, Y.T. Fan, H.W. Hou, Direct degradation of cellulosic biomass to bio-hydrogen from a newly isolated strain *Clostridium sartagoforme* FZ11, *Bioresour. Technol.* 192 (2015) 60–67.
<https://doi.org/10.1016/j.biortech.2015.05.034>.
- [119] J. Xu, M.A. Deshusses, Fermentation of swine wastewater-derived duckweed for biohydrogen production, *Int. J. Hydrogen Energy* 40 (2015) 7028–7036.
<https://doi.org/10.1016/j.ijhydene.2015.03.166>.

- [120] R.R. Gonzales, P. Sivagurunathan, A. Parthiban, S.H. Kim, Optimization of substrate concentration of dilute acid hydrolyzate of lignocellulosic biomass in batch hydrogen production, *Int. Biodeterior. Biodegrad.* 113 (2016) 22–27. <https://doi.org/10.1016/j.ibiod.2016.04.016>.
- [121] L.M. Ottaviano, L.R. Ramos, L.S. Botta, M.B. Amâncio Varesche, E.L. Silva, Continuous thermophilic hydrogen production from cheese whey powder solution in an anaerobic fluidized bed reactor: Effect of hydraulic retention time and initial substrate concentration, *Int. J. Hydrogen Energy* 42 (2017) 4848–4860. <https://doi.org/10.1016/j.ijhydene.2016.11.168>.
- [122] P.C. Hallenbeck, Y. Liu, Recent advances in hydrogen production by photosynthetic bacteria, *Int. J. Hydrogen Energy* 41 (2016) 4446–4454. <https://doi.org/10.1016/j.ijhydene.2015.11.090>.
- [123] T. Lepage, M. Kammoun, Q. Schmetz, A. Richel, Biomass-to-hydrogen : A review of main routes production , processes evaluation and techno-economical assessment, *Biomass and Bioenergy* 144 (2021) 105920. <https://doi.org/10.1016/j.biombioe.2020.105920>.
- [124] D. He, Y. Bultel, J.P. Magnin, C. Roux, J.C. Willison, Hydrogen photosynthesis by *Rhodobacter capsulatus* and its coupling to a PEM fuel cell, *J. Power Sources* 141 (2005) 19–23. <https://doi.org/10.1016/j.jpowsour.2004.09.002>.
- [125] R. Zagrodnik, M. Laniecki, The role of pH control on biohydrogen production by single stage hybrid dark- and photo-fermentation, *Bioresour. Technol.* 194 (2015) 187–195. <https://doi.org/10.1016/j.biortech.2015.07.028>.
- [126] B. Hu, Y. Li, S. Zhu, H. Zhang, Y. Jing, D. Jiang, C. He, Z. Zhang, Evaluation

- of biohydrogen yield potential and electron balance in the photo-fermentation process with different initial pH from starch agricultural leftover, *Bioresour. Technol.* 305 (2020) 122900. <https://doi.org/10.1016/j.biortech.2020.122900>.
- [127] Q. Zhang, S. Zhu, Z. Zhang, H. Zhang, C. Xia, Enhancement strategies for photo-fermentative biohydrogen production: A review, *Bioresour. Technol.* 340 (2021) 125601. <https://doi.org/10.1016/j.biortech.2021.125601>.
- [128] Z. Zhang, F. Ai, H. Zhang, H. Zhang, S. Zhu, Q. Zhang, Y. Li, Synergetic Effect Evaluation of Light and Mass Transfer Enhancement Strategies on Photo Fermentative Biohydrogen Production Process: Illumination, Oscillation, and High Solid Level, *Energy* 269 (2023) 126841. <https://doi.org/10.1016/j.energy.2023.126841>.
- [129] G. Melitos, X. Voulkopoulos, A. Zabaniotou, Waste to Sustainable Biohydrogen Production Via Photo-Fermentation and Biophotolysis – A Systematic Review, *Renew. Energy Environ. Sustain.* 6 (2021) 1–19. <https://doi.org/10.1051/rees/2021047>.
- [130] P.R. Yaashikaa, M. Keerthana Devi, P. Senthil Kumar, Biohydrogen production: An outlook on methods, constraints, economic analysis and future prospect, *Int. J. Hydrogen Energy* 47 (2022) 41488–41506. <https://doi.org/10.1016/j.ijhydene.2022.07.082>.
- [131] K. Bareiß, C. de la Rua, M. Möckl, T. Hamacher, Life cycle assessment of hydrogen from proton exchange membrane water electrolysis in future energy systems, *Appl. Energy* 237 (2019) 862–872. <https://doi.org/10.1016/j.apenergy.2019.01.001>.
- [132] G.D. Saratale, R.G. Saratale, J.R. Banu, J.S. Chang, Biohydrogen Production

From Renewable Biomass Resources, Elsevier B.V., 2019.

<https://doi.org/10.1016/B978-0-444-64203-5.00010-1>.

- [133] P.R. Lanjekar, N.L. Panwar, A Review on Hydrogen Production from Biomass and Commercialization Assessment Through Technology Readiness Levels (TRLs), *Bioenergy Res.* 17 (2024) 912–931.
<https://doi.org/10.1007/s12155-023-10697-1>.
- [134] M. Shahbaz, T. Al-Ansari, A. Inayat, M. Inayat, Technical readiness level of biohydrogen production process and its value chain, *Value-Chain of Biofuels.* (2022) 335-355. <https://doi.org/10.1016/B978-0-12-824388-6.00017-8>.
- [135] A. Arregi, M. Amutio, G. Lopez, J. Bilbao, M. Olazar, Evaluation of thermochemical routes for hydrogen production from biomass: A review, *Energy Convers. Manag.* 165 (2018) 696–719.
<https://doi.org/10.1016/j.enconman.2018.03.089>.
- [136] M.G. Rasul, M.A. Hazrat, M.A. Sattar, M.I. Jahirul, M.J. Shearer, The future of hydrogen: Challenges on production, storage and applications, *Energy Convers. Manag.* 272 (2022) 116326.
<https://doi.org/10.1016/j.enconman.2022.116326>.
- [137] P. Nikolaidis, A. Poullikkas, A comparative overview of hydrogen production processes, *Renew. Sustain. Energy Rev.* 67 (2017) 597–611.
<https://doi.org/10.1016/j.rser.2016.09.044>.
- [138] M. Wang, G. Wang, Z. Sun, Y. Zhang, D. Xu, Review of renewable energy-based hydrogen production processes for sustainable energy innovation, *Glob. Energy Interconnect.* 2 (2019) 436–443.
<https://doi.org/10.1016/j.gloei.2019.11.019>.

- [139] Johan M Ahlström, Renewable Hydrogen Production From Biomass, Environment Science, Engineering. (2021) 1–25.
https://www.etipbioenergy.eu/images/Renewable_Hydrogen_Production_from_Biomass.
- [140] M.M. Soltani, P. Ahmadi, M. Ashjaee, Techno-economic optimization of a biomass gasification energy system with Supercritical CO₂ cycle for hydrogen fuel and electricity production, Fuel 333 (2023) 126264.
<https://doi.org/10.1016/j.fuel.2022.126264>.
- [141] R.D. Silva-Martínez, O. Aguilar-Juárez, L. Díaz-Jiménez, B.E. Valdez-Guzmán, B. Aranda-Jaramillo, S. Carlos-Hernández, Biological Hydrogen Production Through Dark Fermentation with High-Solids Content: An Alternative to Enhance Organic Residues Degradation in Co-Digestion with Sewage Sludge, Fermentation 11 (2025) 1–22.
<https://doi.org/10.3390/fermentation11070398>.
- [142] S. Genç, H. Koku, A preliminary techno-economic analysis of photofermentative hydrogen production, Int. J. Hydrogen Energy 52 (2024) 212–222. <https://doi.org/10.1016/j.ijhydene.2023.03.475>.
- [143] A. Velazquez Abad, P.E. Dodds, Production of Hydrogen, Elsevier, 2017.
<https://doi.org/10.1016/B978-0-12-409548-9.10117-4>.
- [144] M.A. Hossain, J. Jewaratnam, P. Ganesan, Prospect of hydrogen production from oil palm biomass by thermochemical process – A review, Int. J. Hydrogen Energy 41 (2016) 16637–16655.
<https://doi.org/10.1016/j.ijhydene.2016.07.104>.
- [145] M.A. Qyyum, S. Ismail, S.Q. Ni, I. Ihsanullah, R. Ahmad, A. Khan, A.

Tawfik, A.S. Nizami, M. Lee, Harvesting biohydrogen from industrial wastewater: Production potential, pilot-scale bioreactors, commercialization status, techno-economics, and policy analysis, J. Clean. Prod. 340 (2022) 130809. <https://doi.org/10.1016/j.jclepro.2022.130809>.

LIST OF PUBLICATIONS

- **Neha Sharma**, Priyanka Yadav, Saurav Kumar, **Shivam Yadav**, Sudhir G. Warkar, Anil Kumar. **Hydrogen from Biomass: Pathways, Performance, and Prospects.** *Next Materials*, 13 (2026) 102549. <https://doi.org/10.1016/j.nxmte.2026.102549>.
- Saurav Kumar, **Neha Sharma**, Sachin Kumar, Anil Kumar. **Synthesis of Nitro-substituted quinolinamines via cascade annulations of hetero-2-alkynyl-3-carbonitriles.** *Asian Journal of Organic Chemistry*, Wiley. (under revision)



Review article

Hydrogen from biomass: Pathways, performance, and prospects

Neha Sharma, Priyanka Yadav, Saurav Kumar, Shivam Yadav, Sudhir G. Warkar, Anil Kumar^{*}

Delhi Technological University, Bawana Road, Delhi 110042, India

ARTICLE INFO

Keywords:
Biomass
Hydrogen Production
Thermochemical
Biological routes
Pyrolysis
Dark fermentation

ABSTRACT

The production of hydrogen from biomass has shown promise as a sustainable energy source. Biomass is abundant, renewable, and carbon-neutral. It can be effectively used as a feedstock for hydrogen production via a variety of conversion processes, such as thermochemical and biological routes. This article provides a comprehensive overview of common biomass-to-hydrogen pathways. These encompass biological processes such as dark fermentation and phototrophic pathways, as well as thermochemical techniques such as gasification and pyrolysis. While biological pathways enable mild operating conditions and interaction with waste treatment systems, thermochemical technologies generally offer better hydrogen yields and greater technological maturity. Important elements that affect process performance are also covered, including feedstock composition, catalyst choice, reactor design, and system integration. It includes TRL and techno assessment analysis along with the merits and demerits of the techniques used for hydrogen production.

1. Introduction

Nearly 84.5% of the world's energy needs are still met by fossil fuels. In 2023, oil accounted for 32.78% of global energy use, followed by natural gas at 23.96% and coal at 27.79%. Consequently, energy-related greenhouse gas emissions are predicted to reach 378.3 Gt CO₂ in 2024 representing a year-over-year increase of approximately 1% (357 Mt CO₂) [1,2]. As fossil fuel reserves become scarcer, prices increase, and the environmental effects of increasing energy demand escalate, researchers are exploring alternatives to fossil fuels such as low-carbon alternatives and renewable energy resources [3].

The renewable energy industry is regarded today as being one of the cleanest forms of energy available, almost emission-free, because it draws its energy from natural phenomena such as wind, sunlight, biomass, geothermal heat, ocean currents, and hydropower, which are replenished on human timescales and produce significantly lower greenhouse gas emissions than fossil fuels. Globally, final energy demand is divided into four primary sectors: industry, transportation, buildings, and agriculture [4]. In comparison to fossil energy, renewable energy has lower local air pollution burdens, significantly lower life-cycle greenhouse gas emissions, an inexhaustible primary resource base, and often lower operating expenses. The diversification of renewable energy sources also strengthens energy security by reducing dependency on imported fuels. Due to the fact that these technologies are available

across most geographies, nearly every nation can deploy some combination of them [5].

Within this landscape, bioenergy is distinctive and can also serve as a feedstock for low-carbon hydrogen, enabling decarbonization beyond the power sector [6]. Hence, renewable forms of energy are the most promising alternative in the coming years. Fig. 1, summarizes the principal renewable modalities and typical implementations.

1.1. Background and motivation: Global status of renewable energy

The status of primary energy consumption (includes both renewable and non-renewable energy sources) across multiple regions from 2021 to 2024 is presented in Fig. 2.

While the renewable sources include wind energy, solar energy, bioenergy, and geothermal power. The data presented in Figs. 3–5 shows a steady annual increase in renewable energy consumption and generation. Renewable energy consumption and generation are highest in the Asia Pacific across all years. The order for renewable energy consumption is Asia Pacific (17.22 EJ) > Europe (10.14 EJ) > North America (8.44 EJ) > South and Central America (3.35 EJ) > Africa (0.47 EJ) > Middle East (0.18 EJ) > Commonwealth of Independent States (0.10 EJ).

With approximately 11.32 EJ, China is the leading consumer of renewable energy in the Asia-Pacific region. This is followed by India

^{*} Corresponding author.

E-mail addresses: nehasharma_24macche53@dtu.ac.in (N. Sharma), priyanka_2k21phdac504@dtu.ac.in (P. Yadav), yasourabhji@gmail.com (S. Kumar), shivam_24macche59@dtu.ac.in (S. Yadav), sgwarkar@dtu.ac.in (S.G. Warkar), anil_kumar@dtu.ac.in (A. Kumar).

<https://doi.org/10.1016/j.nxmate.2026.102549>

Received 3 April 2026; Received in revised form 10 June 2026; Accepted 15 June 2026

Available online 17 June 2026

2949-8228/© 2026 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

Dissertation (1)

Msc

Document Details

Submission ID	62 Pages
trn:oid::27535:143258926	
Submission Date	
Jun 16, 2026, 8:44 PM GMT+5:30	11,303 Words
Download Date	72,378 Characters
Jun 16, 2026, 9:09 PM GMT+5:30	
File Name	
Dissertation (1).docx	
File Size	
2.0 MB	

4% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Filtered from the Report

- Bibliography
- Quoted Text
- Cited Text
- Small Matches (less than 10 words)

Match Groups

- 27 Not Cited or Quoted 4%
Matches with neither in-text citation nor quotation marks
- 0 Missing Quotations 0%
Matches that are still very similar to source material
- 0 Missing Citation 0%
Matches that have quotation marks, but no in-text citation
- 0 Cited and Quoted 0%
Matches with in-text citation present, but no quotation marks

Top Sources

- 1% Internet sources
- 3% Publications
- 2% Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

*% detected as AI

AI detection includes the possibility of false positives. Although some text in this submission is likely AI generated, scores below the 20% threshold are not surfaced because they have a higher likelihood of false positives.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.