

INDEX

| Content | Page no. |
|---|----------|
| 1. Introduction | 2 |
| 2. Primary elements of the pushover analysis | 2 |
| 3. Procedure to determine the capacity | 2 |
| 4. Procedure to determine the demand | 5 |
| 4.1. Calculating demand displacement using Capacity spectrum method | 5 |
| 4.1.1. Conceptual development of the capacity spectrum Method | 6 |
| 4.1.1.1. Conversion of the capacity curve to the capacity spectrum | 6 |
| 4.1.1.2. Bilinear representation of the capacity spectrum | 9 |
| 4.1.1.3. Estimation of damping and reduction of 5% Damped response spectrum | 10 |
| 4.1.2. Development of demand spectrum | 12 |
| 4.1.3. Intersection of capacity spectrum and demand spectrum | 13 |
| 4.1.4. Calculation of the performance point using procedure A | 13 |
| 4.1.5. Calculation of the performance point using procedure B | 16 |
| 4.1.6. Calculation of the performance point using procedure C | 20 |
| 4.2. Calculating demand displacement using the displacement coefficient Method | 24 |
| 5. Step by step procedure for checking performance at the expected maximum displacement | 27 |
| 6. Illustration of a buildings designed for gravity, earthquake zone 3, zone 4 and zone 5 in SAP 2000 | 29 |
| 7. Conclusion | 53 |
| References | 54 |

